

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 852 442 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
02.11.2000 Bulletin 2000/44

(51) Int Cl.7: **H04N 7/16**, H04N 7/173,
H04N 7/20, H04N 7/10

(21) Application number: **98100142.3**

(22) Date of filing: **02.12.1993**

(54) **Television program delivery system**

Fernsehprogrammverteilungssystem

Système de diffusion de programmes de télévision

(84) Designated Contracting States:
AT BE CH DE DK ES FR GB GR IE IT LI NL PT SE

(30) Priority: **09.12.1992 US 991074**

(43) Date of publication of application:
08.07.1998 Bulletin 1998/28

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
94904814.4 / 0 674 824

(73) Proprietor: **DISCOVERY COMMUNICATIONS, INC.**
Bethesda, MD 20814-3522 (US)

(72) Inventors:
• **Hendricks, John**
Potomac, MA 20854 (US)

• **Bonner, Alfred**
Bethesda, MA 20817 (US)

(74) Representative: **Strehl Schübel-Hopf & Partner**
Maximilianstrasse 54
80538 München (DE)

(56) References cited:
EP-A- 0 187 961 **WO-A-92/21206**
GB-A- 2 177 873 **US-A- 4 805 014**
US-A- 5 144 663

• **OLSHANSKY R ET AL: "SUBSCRIBER
DISTRIBUTION NETWORKS USING
COMPRESSED DIGITAL VIDEO" JOURNAL OF
LIGHTWAVE TECHNOLOGY, vol. 10, no. 11, 1
November 1992, pages 1760-1765, XP000355287**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 852 442 B1

DescriptionRELATED APPLICATIONS

5 **[0001]** This application is a continuation-in-part of application Serial Number 07/991,074 filed December 9, 1992, entitled TELEVISION PROGRAM PACKAGING AND DELIVERY SYSTEM WITH MENU DRIVEN SUBSCRIBER ACCESS. The following publications are also based on the above-referenced patent application: EP-A-0 673 578 to EP-A-0 673 583, EP-A-0 732 027, EP-A-0 732 030, EP-A-0 732 031, and US-A-5 307 627.

TECHNICAL FIELD

[0002] The invention relates to television entertainment systems for providing television programming to consumer homes. More particularly, the invention relates to a user friendly system for providing consumers with television programming choices.

15 **[0003]** Advances in television entertainment have been primarily driven by breakthroughs in technology. In 1939, advances on Vladimir Zworykin's picture tube provided the stimulus for NBC to begin its first regular broadcasts. In 1975, advances in satellite technology provided consumers with increased programming to homes.

[0004] Many of these technology breakthroughs have produced inconvenient systems for consumers. One example is the ubiquitous three remote control home, having a separate and unique remote control for the TV, cable box and VCR. More recently, technology has provided cable users in certain parts of the country with 100 channels of programming. This increased program capacity is beyond the ability of many consumers to use effectively. No method of managing the program choices has been provided to consumers.

20 **[0005]** Consumers are demanding that future advances in television entertainment, particularly programs and program choices, be presented to the consumer in a user friendly manner. Consumer preferences, instead of technological breakthroughs, will drive the television entertainment market for at least the next 20 years. As computer vendors have experienced a switch from marketing new technology in computer hardware to marketing better useability, interfaces and service, the television entertainment industry will also experience a switch from new technology driving the market to consumer useability driving the market.

30 **[0006]** Consumers want products incorporating new technology that are useful, and will no longer purchase new technology for the sake of novelty or status. Technological advances in sophisticated hardware are beginning to surpass the capability of the average consumer to use the new technology. Careful engineering must be done to make entertainment products incorporating new technology useful and desired by consumers.

[0007] In order for new television entertainment products to be successful, the products must satisfy consumer demands. TV consumers wish to go from limited viewing choices to a variety of choices, from no control of programming to complete control. Consumers wish to advance from cumbersome and inconvenient television to easy and convenient television and keep costs down. Consumers do not wish to pay for one hundred channels when due to lack of programming information, they seldom, if ever, watch programming on many of these channels.

35 **[0008]** The concepts of interactive television, high definition television and 300 channel cable systems In consumer homes will not sell if they are not packaged, delivered and presented in a useable fashion to consumers. The problem is that TV programming is not being presented to consumers in a user friendly manner.

[0009] Consumers are already being bombarded with programming options, numerous "free" cable channels, subscription cable channels and pay-per-view choices. Any further increase in TV entertainment choices, without a user friendly presentation and approach, will likely bewilder viewers with a mind-numbing array of choices.

45 **[0010]** WO 92/21206 discloses a cable interconnect system that delivers analog advertisements from a central control facility to cable headends via satellite. The analog advertisements are stored on videotape at the central control facility and delivered to cable headends along with instructions concerning the time and channels on which to play the advertisement. The document discloses the satellite transmission of only a standard, analog television signal from the central control facility to cable headends. It does not disclose or suggest the satellite transmission of more than one digital program signal.

50 **[0011]** EP-A-0 187 961 discloses a satellite scrambling communication network that uses geographically separated uplinks to provide scrambled video and audio signals and descrambling control data to cable television distribution systems as well as separated individual subscribers. The document discloses a business control center that operates to control the access of individual subscribers, subscriber groups, or networks to premium programming channels that are available on geographically separated uplinks, using a master data stream to perform access control. It specifies the master data stream as a digital data signal that may be carried in-channel in a blanking interval or out-of-channel of a standard, analog television signal. The document does not disclose or suggest that the premium program signal whose access is being specified by the master data stream is a digital program signal. Again, this document fails to disclose a satellite transmission of more than one digital program signal from a center to a cable headend.

SUMMARY OF THE INVENTION

[0012] It is an object of the invention to provide a user friendly interface for subscribers to access television programs.

[0013] It is an object of this invention to provide an economical system which can present television programs through a user friendly interface which allows the consumer to easily select from among the many program choices.

[0014] It is an object of this invention to provide a system capable of handling hundreds of programs in different formats, be expandable for future types of programming and be inexpensive.

[0015] It is an object of this invention to provide a system for organizing programming to be offered to viewers.

[0016] It is an object of this invention to provide a television program delivery system that can be operated in a distributive fashion and controlled from one or more national centers.

[0017] It is an object of this invention to provide a television program delivery system that operates in the digital audio/video environment.

[0018] It is an object of this invention to provide a system capable of packaging hundreds of television programs for delivery to subscribers.

[0019] It is an object of this invention to provide a system that analyzes data on programs watched by viewers.

[0020] It is an object of this invention to provide a system capable of monitoring account and billing information for hundreds of program offerings.

[0021] It is an object of this invention to provide a system that assists the consumer with program selection.

[0022] It is an object of this invention to provide a system that provides subscribers with menu-driven access to hundreds of television programs.

[0023] It is an object of this invention to provide a system that accommodates digital decompression and digital signaling capabilities.

[0024] In accordance with the invention, the above objects are met by the systems defined in claims 1 and 16.

[0025] The invention makes use of developments in digital compression signaling that allows much greater throughput of television program signals over existing transmission media. These developments allow subscribers to use the present invention to exploit a four-fold or more increase in current program delivery capability. In particular, the present invention provides subscribers with a menu-driven access scheme to an expanded television program lineup, enabling subscribers to access and view selected programs using a user friendly interface.

[0026] This interface includes a remote control and a series of menus that may be sequenced by the subscriber using simple alpha, numeric and iconic character access keys, or by moving a cursor or highlight bar on the television screen. In this way, subscribers can advance from one menu to the next with the press of a single button. Different television programs, grouped by category, may be selected and accessed from each menu. As a result, the present invention provides subscribers with a convenient method of choosing a program for viewing from hundreds of program offerings.

[0027] An embodiment of the invention uses several basic system components, namely: (i) at least one operations center, where the television programs are packaged and control information is created and then assembled in the form of digital data, (ii) a digital compression system, where the television programming signals and digital data may be compressed and processed for digital transmission over satellite to a cable headend for subsequent distribution over a cable network, and (iii) a set of in-home decompressors or set top terminals, which provide subscribers with digital decompression, digital signaling and menu generation capabilities. Each of these basic system components plays an important role in the system's overall operation.

[0028] The operations center includes a computer assisted packaging system (CAP), which makes use of the necessary hardware and software to control and transmit programming signals over a television delivery system. The CAP creates the program lineup or packaging of programs and the packaging of menu and control information for later transmission and use at the cable headend. Transmission of control information enables the operations center to change allocation of programs across physical channels, update menu information, reprogram menu formats and menu flow, and change or augment a packaged program signal sent to a particular region of the country.

[0029] Once the programming signals have been packaged, compressed and processed for digital transmission, these signals are sent along with the control information to the cable headend. Each cable headend typically includes signal processing hardware and software capable of receiving, repackaging/combining and routing program signals to the subscriber homes.

[0030] Each cable headend in the television delivery system also includes a network controller that manages the configuration of the set top terminals and processes signals received from the set top terminals, gathering programs watched data. The network controller modifies the control information to accommodate changes and additions in programming and advertisements, working with the signal processing hardware and software to distribute programs to the subscribers. The network controller also monitors all data received from the set top terminals in the cable network. The network controller uses data received to target advertisements to particular subscribers as well as to maintain account and billing information.

[0031] From the cable headend, the programming signals and program control information are transmitted to the subscriber locations. Each subscriber is equipped with a set top terminal having various digital decompression, menu generation, upstream data transmissions, remote reprogramming and other advanced functional capabilities, or some combination thereof. With such capabilities, the set top terminal supports, for example, interactive communications with the cable headend. The set top terminal includes an interface that allows a subscriber to select and decompress a digitally compressed program signal for display on a television through sequencing menus on the television screen. The menus may be generated from menu templates stored in each set top terminal, with each selectable menu option corresponding to either another menu or a particular television program.

[0032] Embodiments of the invention will now be described in more detail by reference to the attached drawings.

DESCRIPTION OF THE DRAWINGS

[0033] Figure 1 is a diagram of the primary components of the television delivery system.

[0034] Figure 2 is an overview of the television delivery system operations.

[0035] Figure 3 is a schematic of the operation of the primary components of the system.

[0036] Figure 4 is a block diagram of the hardware components of the set top terminal.

[0037] Figure 5a is a perspective front view of a set top terminal.

[0038] Figure 5b is a perspective rear view of a set top terminal.

[0039] Figure 6 is a schematic of a Turbo card upgrade for a set top terminal.

[0040] Figure 7a is a drawing of a frame format for a program control information signal.

[0041] Figure 7b is a drawing of a frame format for a polling response from the set top terminal.

[0042] Figure 8 is a drawing of the basic menus used in the present invention, including ten major menus represented by icons.

[0043] Figure 9a is a drawing of storage for on-screen menu templates and other graphics files stored in graphics memory of the set top terminal.

[0044] Figure 9b is a drawing showing the hierarchical storage of text in memory for the set top terminal.

[0045] Figure 9c is a drawing of a flow chart showing the steps required for the microprocessor to retrieve, combine and display a menu.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A. Television Program Delivery System Description

1. Introduction

[0046] Figure 1 shows the present invention as an expanded cable television program delivery system 200 that dramatically increases programming capacity using compressed transmission of television program signals. Developments in digital bandwidth compression technology now allow much greater throughput of television program signals over existing or slightly modified transmission media. The program delivery system 200 shown provides subscribers with a user friendly interface to operate and exploit a six-fold or more increase in current program delivery capability.

[0047] Subscribers are able to access an expanded television program package and view selected programs through a menu-driven access scheme that allows each subscriber to select individual programs by sequencing a series of menus. The menus are sequenced by the subscriber using simple alpha-numeric and iconic character access or moving a cursor or highlight bar on the TV screen to access desired programs by simply pressing a single button, rather than recalling from memory and pressing the actual two or more digit numeric number assigned to a selection. Thus, with the press of a single button, the subscriber can advance from one menu to the next. In this fashion, the subscriber can sequence the menus and select a program from any given menu. The programs are grouped by category so that similar program offerings are found on the same menu.

2. Major System Components

[0048] In its most basic form, the system uses a program delivery system 200 in conjunction with a conventional concatenated cable television system 210. The program delivery system 200 generally includes (i) at least one operations center 202, where program packaging and control information are created and then assembled in the form of digital data, (ii) a digital compression system, where the digital data is compressed, combined/multiplexed, encoded, and mapped into digital signals for satellite transmission to the cable headend 208, and (iii) a set of in-home decompressors. The program delivery system 200 transports the digital signals to the cable headend 208 where the signals are transmitted through a concatenated cable television system 210. Within the cable headend 208, the received

signals may be decoded, demultiplexed, managed by a local central distribution and switching mechanism, combined and then transmitted to the set top terminal 220 located in each subscriber's home over the cable system 210. Although concatenated cable systems 210 are the most prevalent transmission media to the home, telephone lines, cellular networks, fiberoptics, Personal Communication Networks and similar technology for transmitting to the home can be used interchangeably with this program delivery system 200.

[0049] The delivery system 200 has a reception region 207 with an in-home decompression capability. This capability is performed by a decompressor housed within a set top terminal 220 in each subscriber's home. The decompressor remains transparent from the subscriber's point of view and allows any of the compressed signals to be demultiplexed and individually extracted from the composite data stream and then individually decompressed upon selection by the subscriber. The decompressed video signals are converted into analog signals for television display. Such analog signals include NTSC formatted signals for use by a standard television. Control signals are likewise extracted and decompressed and then either executed immediately or placed in local storage such as a RAM. Multiple sets of decompression hardware may be used to decompress video and control signals. The set top terminal 220 may then overlay or combine different signals to form the desired display on the subscriber's television. Graphics on video or picture-on-picture are examples of such a display.

[0050] Although a single digital compression standard (e.g., MPEG) may be used for both the program delivery system 200 and the concatenated cable system 210, the compression technique used may differ between the two systems. When the compression standards differ between the two media, the signals received by the cable headend 208 must be decompressed before transmission from the headend 208 to the set top terminals 220. Subsequently, the cable headend 208 must recompress and transmit the signals to the set top terminal 220, which would then decompress the signals using a specific decompression algorithm.

[0051] The video signals and program control signals received by the set top terminal 220 correspond to specific television programs and menu selections that each subscriber may access through a subscriber interface. The subscriber interface is a device with buttons located on the set top terminal 220 or on a portable remote control 900. In the preferred system embodiment, the subscriber interface is a combined alpha-character, numeric and iconic remote control device 900, which provides direct or menu-driven program access. The preferred subscriber interface also contains cursor movement and go buttons as well as alpha, numeric and iconic buttons. This subscriber interface and menu arrangement enables the subscriber to sequence through menus by choosing from among several menu options that are displayed on the television screen. In addition, a user may bypass several menu screens and immediately choose a program by selecting the appropriate alpha-character, numeric or iconic combinations on the subscriber interface. In the preferred embodiment, the set top terminal 220 generates the menus that are displayed on the television by creating arrays of particular menu templates, and the set top terminal 220 displays a specific menu or submenu option for each available video signal.

3. Operations Center and Digital Compression System

[0052] The operations center 202 performs two primary services, packaging television programs and generating the program control information signal. At the operations center 202, television programs are received from external program sources in both analog and digital form. Figure 2 shows an embodiment of the operations center receiving signals from various external sources 212. Examples of the external program sources are sporting events, children's programs, specialty channels, news or any other program source that can provide audio or visual signals. Once the programs are received from the external program sources, the operations center 202 digitizes (and preferably compresses) any program signals received in analog form. The operations center 202 may also maintain an internal storage of programs. The internally stored programs may be in analog or digital form and stored on permanent or volatile memory sources, including magnetic tape or RAM. Subsequent to receiving programming, the operations center 202 packages the programs into the groups and categories which provide the optimal marketing of the programs to subscribers. For example, the operations center 202 may package the same programs into different categories and menus for weekday, prime-time viewing and Saturday afternoon viewing. Also, the operations center 202 packages the television programs in a manner that enables both the various menus to easily represent the programs and the subscribers to easily access the programs through the menus.

[0053] The packaging of the digital signals is typically performed at the operations center 202 by computer assisted packaging equipment (CAP). The CAP system normally includes at least one computer monitor, keyboard, mouse, and standard video editing equipment. A programmer packages the signals by entering certain information into the CAP. This information includes the date, time slot, and program category of the various programs. The programmer and the CAP utilize demographic data and ratings in performing the packaging tasks. After the programmer selects the various programs from a pool of available programs and inputs the requisite information, the programmer, with assistance from the CAP, can select the price and allocate transponder space for the various programs. After the process is complete, the CAP displays draft menus or program schedules that correspond to the entries of the pro-

grammer. The CAP may also graphically display allocation of transponder space. The programmer may edit the menus and transponder allocation several times until satisfied with the programming schedule. During the editing, the programmer may direct the exact location of any program name on a menu with simple commands to the CAP.

[0054] The packaging process also accounts for any groupings by satellite transponder which are necessary. The operations center 202 may send different groups of programs to different cable headends 208 and/or set top terminals 220. One way the operations center 202 may accomplish this task is to send different program packages to each transponder. Each transponder, or set of transponders, then relays a specific program package to specific cable headends 208 and/or set top terminals 220. The allocation of transponder space is an important task performed by the operations center 202.

[0055] The operations center 202 may also "insert" directions for filling local available program time in the packaged signal to enable local cable and television companies to fill the program time with local advertising and/or local programming. Consequently, the local cable headends 208 are not constrained to show only programs transmitted from the operations center 202. New set top converters will incorporate both digital and analog channels. Therefore, the cable headend 208 may combine analog signals with the digital signals prior to transmitting the program signals to the set top terminals 220.

[0056] After the CAP packages the programs, it creates a program control information signal to be delivered with the program package to the cable headend 208 and/or set top terminal 220. The program control information signal contains a description of the contents of the program package, commands to be sent to the cable headend 208 and/or set top terminal 220, and other information relevant to the signal transmission.

[0057] In addition to packaging the signal, the operations center 202 employs digital compression techniques to increase existing satellite transponder capacity by at least a 4:1 ratio, resulting in a four-fold increase in program delivery capability. A number of digital compression algorithms currently exist which can achieve the resultant increase in capacity and improved signal quality desired for the system. The algorithms generally use one or more of three basic digital compression techniques: (1) within-frame (intraframe) compression, (2) frame-to-frame (interframe) compression, and (3) within carrier compression. Specifically, in the preferred embodiment, the MPEG 2 compression method is used. After digital compression, the signals are combined (multiplexed) and encoded. The combined signal is subsequently transmitted to various uplink sites 204.

[0058] There may be a single uplink site 204 or multiple uplink sites (represented by 204', shown in phantom in Figure 1) for each operation center 202. The uplink sites 204 may either be located in the same geographical place or may be located remotely from the operations center 202. Once the composite signal is transmitted to the uplink sites 204, the signal may be multiplexed with other signals, modulated, upconverted and amplified for transmission over satellite. Multiple cable headends 208 may receive such transmissions.

[0059] In addition to multiple uplinks, the delivery system 200 may also contain multiple operations centers. The preferred method for using multiple operations centers is to designate one of the operations centers as a master operations center and to designate the remaining operations centers as slave operations centers. In this configuration, the master operations center coordinates various functions among the slave operations centers such as synchronization of simultaneous transmissions and distributes the operations workload efficiently.

4. Cable Headend

[0060] After the operations center 202 has compressed and encoded the program signals and transmitted the signals to the satellite, the cable headend 208 receives and further processes the signals before they are relayed to each set top terminal 220. Each cable headend site is generally equipped with multiple satellite receiver dishes. Each dish is capable of handling multiple transponder signals from a single satellite and sometimes from multiple satellites.

[0061] As an intermediary between the set top terminals 220 and the operations center 202 (or other remote site), the cable headend 208 performs two primary functions. First, the cable headend 208 acts as a distribution center, or signal processor, by relaying the program signal to the set top terminal 220 in each subscriber's home. In addition, the cable headend 208 acts as a network controller 214 by receiving information from each set top terminal 220 and passing such information on to an information gathering site such as the operations center 202.

[0062] Figure 3 shows an embodiment where the cable headend 208 and the subscriber's home are linked by certain communications media 216. In this particular embodiment, analog signals, digitally compressed signals, other digital signals and up-stream/interactivity signals are sent and received over the media 216. The cable headend 208 provides such signaling capabilities in its dual roles as a signal processor 209 and network controller 214.

[0063] As a signal processor 209, the cable headend 208 prepares the program signals that are received by the cable headend 208 for transmission to each set top terminal 220. In the preferred system, the signal processor 209 re-routes or demultiplexes and recombines the signals and digital information received from the operations center 202 and allocates different portions of the signal to different frequency ranges. Cable headends 208 which offer different subscribers different program offerings may allocate the program signals from the operations center 202 in various

manners to accommodate different viewers. The signal processor 209 may also incorporate local programming and/or local advertisements into the program signal and forward the revised signal to the set top terminals 220. To accommodate this local programming availability, the signal processor 209 must combine the local signal in digital or analog form with the operations center program signals. If the local cable system uses a compression standard that is different than the one used by the operations center 202, the signal processor 209 must also decompress and recompress incoming signals so they may be properly formatted for transmission to the set top terminals 220. This process becomes less important as standards develop (i.e., MPEG 2). In addition, the signal processor 209 performs any necessary signal decryption and/or encryption.

[0064] As a network controller 214, the cable headend 208 performs the system control functions for the system. The primary function of the network controller 214 is to manage the configuration of the set top terminals 220 and process signals received from the set top terminals 220. In the preferred embodiment, the network controller 214 monitors, among other things, automatic poll-back responses from the set top terminals 220 remotely located at each subscribers' home. The polling and automatic report-back cycle occurs frequently enough to allow the network controller 214 to maintain accurate account and billing information as well as monitor authorized channel access. In the simplest embodiment, information to be sent to the network controller 214 will be stored in RAM within each subscriber's set top terminal 220 and will be retrieved only upon polling by the network controller 214. Retrieval may, for example, occur on a daily, weekly or monthly basis. The network controller 214 allows the system to maintain complete information on all programs watched using a particular set top terminal 220.

[0065] The network controller 214 is also able to respond to the immediate needs of a set top terminal 220 by modifying a program control information signal received from the operations center 202. Therefore, the network controller 214 enables the delivery system to adapt to the specific requirements of individual set top terminals 220 when the requirements cannot be provided to the operations center 202 in advance. In other words, the network controller 214 is able to perform "on the fly programming" changes. With this capability, the network controller 214 can handle sophisticated local programming needs such as, for example, interactive television services, split screen video, and selection of different foreign languages for the same video. In addition, the network controller 214 controls and monitors all compressors and decompressors in the system.

[0066] The delivery system 200 and digital compression of the preferred embodiment provides a one-way path from the operations center 202 to the cable headend 208. Status and billing information is sent from the set top terminal 220 to the network controller 214 at the cable headend 208 and not directly to the operations center 202. Thus, program monitoring and selection control will take place only at the cable headend 208 by the local cable company and its decentralized network controllers 214 (i.e., decentralized relative to the operations center 202, which is central to the program delivery system 200). The local cable company will in turn be in communication with the operations center 202 or a regional control center (not shown) which accumulates return data from the set top terminal 220 for statistical or billing purposes. In alternative system embodiments, the operations center 202 and the statistical and billing sites are collocated. Further, telephone lines with modems are used to transfer information from the set top terminal 220 to the statistical and billing sites.

5. Set Top Terminal

[0067] The set top terminal 220 is the portion of the delivery system 200 that resides in the home of a subscriber. The set top terminal 220 is usually located above or below the subscriber's television, but it may be placed anywhere in or near the subscriber's home as long as it is within the range of the subscriber's remote control device 900. In some aspects, the set top terminal 220 may resemble converter boxes already used by many cable systems. For instance, each set top terminal 220 may include a variety of error detection, decryption, and coding techniques such as anti-taping encoding. However, it will become apparent from the discussion below that the set top terminal 220 is able to perform many functions that an ordinary converter box cannot perform.

[0068] The set top terminal 220 has a plurality of input and output ports to enable it to communicate with other local and remote devices. The set top terminal 220 has an input port that receives information from the cable headend 208. In addition, the unit has at least two output ports which provide communications from the set top terminal 220 to a television and a VCR. Certain menu selections may cause the set top terminal 220 to send control signals directly to the VCR to automatically program or operate the VCR. Also, the set top terminal 220 contains a phone jack which can be used for maintenance, trouble shooting, reprogramming and additional customer features. The set top terminal 220 may also contain stereo/audio output terminals and a satellite dish input port.

[0069] Functionally, the set top terminal 220 is the last component in the delivery system chain. The set top terminal 220 receives compressed program and control signals from the cable headend 208 (or, in some cases, directly from the operations center 202). After the set top terminal 220 receives the individually compressed program and control signals, the signals are demultiplexed, decompressed, converted to analog signals (if necessary) and either placed in local storage (from which the menu template may be created), executed immediately, or sent directly to the television

screen.

[0070] After processing certain signals received from the cable headend 208, the set top terminal 220 is able to store menu templates for creating menus that are displayed on a subscriber's television by using an array of menu templates. Before a menu can be constructed, menu templates must be created and sent to the set top terminal 220 for storage.

A microprocessor uses the control signals received from the operations center 202 or cable headend 208 to generate the menu templates for storage. Each menu template may be stored in volatile memory in the set top terminal 220. When the set top terminal receives template information it demultiplexes the program control signals received from the cable headend 208 into four primary parts: video, graphics, program logic and text. Each menu template represents a different portion of a whole menu, such as a menu background, television logo, cursor highlight overlay, or other miscellaneous components needed to build a menu. The menu templates may be deleted or altered using control signals received from the operations center 202 or cable headend 208.

[0071] Once the menu templates have been stored in memory, the set top terminal 220 can generate the appropriate menus. In the preferred embodiment, the basic menu format information is stored in memory located within the set top terminal 220 so that the microprocessor may locally access the information from the set top terminal instead of from an incoming signal. The microprocessor next generates the appropriate menus from the menu templates and the other menu information stored in memory. The set top terminal 220 then displays specific menus on the subscriber's television screen that correspond to the inputs the subscriber selects.

[0072] If the subscriber selects a specific program from a menu, the set top terminal 220 determines on which channel the program is being shown, demultiplexes and extracts the single channel transmitted from the cable headend 208. The set top terminal 220 then decompresses the channel and, if necessary, converts the program signal to an analog NTSC signal to enable the subscriber to view the selected program. The set top terminal 220 can be equipped to decompress more than one program signal, but this would unnecessarily add to the cost of the unit since a subscriber will generally only view one program at a time. However, two or three decompressors may be desirable to provide picture-on-picture capability, control signal decompression, enhanced channel switching or like features.

[0073] In addition to menu information, the set top terminal 220 may also store text transmitted from the cable headend 208 or the operations center 202. The text may inform the subscriber about upcoming events, billing and account status, new subscriptions, or other relevant information. The text will be stored in an appropriate memory location depending on the frequency and the duration of the use of the textual message.

[0074] Also, optional upgrades are available to enhance the performance of a subscriber's set top terminal 220. These upgrades may consist of a cartridge or computer card (not shown) that is inserted into an expansion slot in the set top terminal 220 or may consist of a feature offered by the cable headend 208 or operations center 202 to which the user may subscribe. Available upgrades may include on line data base services, interactive multi-media services, access to digital radio channels, and other services.

[0075] In the simplest embodiment, available converter boxes such as those manufactured by General Instruments or Scientific Atlanta, may be modified and upgraded to perform the functions of a set top terminal 220. The preferred upgrade is a circuit card with a microprocessor which is electronically connected to or inserted into the converter box.

6. Remote Control Device

[0076] The primary conduit for communication between the subscriber and the set top terminal 220 is through the subscriber interface, preferably a remote control device 900. Through this interface, the subscriber may select desired programming through the system's menu-driven scheme or by directly accessing a specific channel by entering the actual channel number. Using the interface, the subscriber can navigate through a series of informative program selection menus. By using menu-driven, iconic or alpha-character access, the subscriber can access desired programs by simply pressing a single button rather than recalling from memory and pressing the actual channel number to make a selection. The subscriber can access regular broadcast and basic cable television stations by using either the numeric keys on the remote control 900 (pressing the corresponding channel number), or one of the menu icon selection options.

[0077] In addition to enabling the subscriber to easily interact with the cable system 200, the physical characteristics of the subscriber interface 900 should also add to the user friendliness of the system. The remote control 900 should easily fit in the palm of the user's hand. The buttons of the preferred remote control 900 contain pictorial symbols that are easily identifiable by the subscriber. Also, buttons that perform similar functions may be color coordinated and consist of distinguishing textures to increase the user friendliness of the system.

7. Menu-Driven Program Selection

[0078] The menu-driven scheme provides the subscriber with one-step access to all major menus, ranging from hit movies to sport specials to specialty programs. From any of the major menus, the subscriber can in turn access sub-menus and minor menus by cursor or alpha-character access.

[0079] There are two different types of menus utilized by the preferred embodiment, the Program Selection menus and the During Program menus. The first series of menus, Program Selection menus, consists of an Introductory, a Home, Major menus, and Submenus. The second series of menus, During Program menus, consists of two primary types, Hidden menus and the Program Overlay menus.

5 [0080] Immediately after the subscriber turns on the set top terminal 220, the Introductory menu welcomes the subscriber to the system. The Introductory menu may display important announcements from the local cable franchise, advertisements from the cable provider, or other types of messages. In addition, the Introductory menu can inform the subscriber if the cable headend 208 has sent a personal message to the subscriber's particular set top terminal 220.

10 [0081] After the Introductory menu has been displayed the subscriber may advance to the next level of menus, namely the Home menu. In the preferred embodiment, after a certain period of time, the cable system will advance the subscriber by default to the Home menu. From the Home menu, the subscriber is able to access all of the programming options. The subscriber may either select a program directly by entering the appropriate channel number from the remote control 900, or the subscriber may sequence through incremental levels of menu options starting from the Home menu. The Home menu lists categories that correspond to the first level of menus called Major menus.

15 [0082] If the subscriber chooses to sequence through subsequent menus, the subscriber will be forwarded to the Major menu that corresponds to the chosen category from the Home menu. The Major menus further refine a subscriber's search and help guide the subscriber to the selection of his choice.

[0083] From the Major menus, the subscriber may access several submenus. From each submenu, the subscriber may access other submenus until the subscriber finds a desired television program. Similar to the Major menu, each successive level of Submenus further refines the subscriber's search. The system also enables the subscriber to skip certain menus or submenus and directly access a specific menu or television program by entering the appropriate commands on the remote control 900.

20 [0084] The During program menus (including Hidden Menus and Program Overlay Menus) are displayed by the set top terminal 220 only after the subscriber has selected a television program. In order to avoid disturbing the subscriber, the set top terminal 220 does not display the Hidden Menu until the subscriber selects the appropriate option to display a Hidden Menu. The Hidden Menus contain options that are relevant to the program selected by the viewer. For example, a Hidden Menu may contain options that enable a subscriber to enter an interactive mode or escape from the selected program.

25 [0085] Program Overlay Menus are similar to Hidden Menus because they occur during a program and are related to the program being viewed. However, the Program Overlay Menus are displayed concurrently with the program selected by the subscriber. Most Program Overlay Menus are small enough on the screen to allow the subscriber to continue viewing the selected program comfortably.

35 B. Detailed Set Top Terminal Description

[0086] The set top terminal 220 receives and manipulates signals from the cable headend 208. The set top terminal 220 is equipped with local computer memory and the capability of interpreting the digitally compressed signal to produce menus for the subscriber. The remote control 900 communicates the subscriber's selections to the set top terminal 220. The subscriber's selections are generally based upon menus or other prompts displayed on the television screen.

40 [0087] It is preferred that the signal reaches the subscriber's home in a compressed format and is decompressed prior to viewing. Included in the delivered program signal is information that enables equipment at the subscriber's home to display menus for choosing particular programs. Depending on the particular embodiment, the television program signal may arrive at the subscriber's home through one or more connections such as coaxial cables, fiber cables, twisted pairs, cellular telephone connections, or personal communications network (PCN) hookups.

45 [0088] The program control information signal is generated by the operations center 202 and provides the network controller 214 with data on the scheduling and description of programs. In an alternate configuration, this data is sent directly to the set top terminal 220 for display to the subscriber. In the preferred embodiment, the program control information signal is stored and modified by the network controller 214 and sent to the set top terminal 220 in the form of a set top terminal control information stream (STTCIS). The set top terminal 220 integrates either the program control information signal or the STTCIS with data stored in the memory of the set top terminal 220 to generate on-screen menus that assist the subscriber in choosing programs for display.

50 [0089] The types of information that can be sent using the program control signal include: number of program categories, names of program categories, what channels are assigned to a specific category (such as specialty channels), names of channels, names of programs on each channel, program start times, length of programs, description of programs, menu assignment for each program, pricing, whether there is a sample video clip for advertisement for the program, and any other program, menu or product information.

55 [0090] With a minimal amount of information being communicated to the set top terminal 220 on a regular basis, the set top terminal 220 is able to determine the proper menu location for each program and the proper time and channel

to activate for the subscriber after a menu selection. The program control information signal and STTCIS can be formatted in a variety of ways and the on-screen menus can be produced using many different methods. For instance, if the program control information signal carries no menu format information, the menu format for creating the menus can be fixed in ROM at the set top terminal 220. In the preferred embodiment, the menu format information is stored at the set top terminal 220 in a temporary memory device such as a RAM or EPROM. New menu format information is sent via the program control information signal or the STTCIS to the set top terminals 200 whenever a change to a menu format is desired.

[0091] In the simplest embodiment, the menu formats remain fixed and only the text changes. In this way the program control information signal can be limited to primarily text and a text generator can be employed in the set top terminal 220. Another simple embodiment uses a separate channel full-time (large bandwidth) just for the menu information.

[0092] Live video signals may be used in windows of certain menus. These video signals can be transmitted using the program control information signal or STTCIS, or can be taken off channels being transmitted simultaneously with the menu display. Video for menus, promos or demos may be sent to the set top terminal 220 in several formats, including (1) on a dedicated channel, (2) on a regular program channel and scaled to size, or (3) along with the program control information signal. However, in the preferred embodiment, a large number of short promos or demo video is sent using a split screen technique on a dedicated channel. A multiple window technique may be used with the menus to display a description of a program and one or more video frames that assist the subscriber in selecting the program.

[0093] Figure 4 shows the basic hardware components of the set top terminal 220. The set top terminal 220 has a tuner 603, digital demodulator 606, decryptor 600, and demultiplexers 609, 616 as well as audio equipment 612 and a remote control interface 626 for receiving and processing signals from the remote control unit 900. An optional modem 627 allows communication between a microprocessor 602 and the cable headend 208. An NTSC encoder 625 provides a standard NTSC video output.

[0094] The microprocessor 602 is capable of executing program instructions stored in memory. These instructions allow a user to access various menus by making selections on the remote control 900.

[0095] The manner in which the video is decompressed and the menus are generated from the program control information signal or STTCIS varies depending on the specific embodiment of the invention. Video decompressors 618 and 622 may be used if the video is compressed. The program control information signal may be demultiplexed into its component parts, and a video decompressor 618, graphic decompressor, text generator and video combiner 624 may be used to assist in creating the menus.

[0096] In addition to the menu format information that is stored in graphics memory, the set top terminal 220 also stores data tracking those programs that have been selected for viewing. By gathering this data, the set top terminal 220 can maintain an accurate record of all programs accessed/watched by storing the data in EEPROM or RAM. Subsequently, this data can be transmitted to the cable headend 208, where it can be used in carrying out network control and monitoring functions. Such data transmissions between the set top terminal 220 and cable headend 208 can be accomplished, for example, through upstream transmission over the cable network or over telephone lines through the use of telephone modems. Where upstream transmission over the cable network is used, the set top terminals 220 can complete data transmissions on a scheduled (e.g., using a polling response or status report to respond to polling requests sent from the cable headend 208) or as-needed (e.g., using a random access technique) basis.

[0097] Figure 5a shows the front panel of the set top terminal 220, which includes an infrared sensor 630 and a series of LED displays 640. The LED displays 640 may indicate with an icon or a letter (e.g. A-K) the major menu currently selected by the set top terminal 220 or the channels selected directly by a user, or menu channel selections (e.g., from 1 to 50). Further displays may include current channel, time, volume level, sleep time, parental lock (security), account balance, use of a hardware upgrade, second channel being recorded by VCR, use of the Level D music hardware upgrade in a separate room, and any other displays useful to a subscriber to indicate the current status of the set top terminal 220. The LEDs 640 may also provide an indication of the digital audio channel currently tuned.

[0098] The set top terminal 220 includes a flapped opening 635 on its front that allows the insertion of a magnetic cartridge (or similar portable storage device, including optical disk, ROM, EPROM, etc. not shown). This cartridge opening 635 allows the set top terminal 220 to be upgraded or reprogrammed locally with the use of a magnetic tape cartridge.

[0099] On the top or cover of the set top terminal 220 are located pushbutton controls 645. Any function that can be performed on the remote 900 may also be performed at the set top terminal 220 using the duplicative pushbutton controls 645.

[0100] Figure 5b shows the back of the set top terminal 220, which includes a pair of output terminals 650, pair of input terminals 652, pair of stereo/audio output terminals 654, satellite dish input port 656, telephone jack 658 and an RS-422 port 660. In addition, an upgrade port 662 and a cover plate 664 are held in place by a series of sheet metal screws. One of the output terminals 650 is for a television and the other is for a VCR. The set top terminal 220 is equipped to handle incoming signals on one or two cables using the input terminals 652. The phone jack 658 and an

RS-232 or RS-422 port 660 are provided for maintenance, trouble shooting, reprogramming and additional customer features. In alternate embodiments, the telephone jack 658 may be used as the primary mode of communication between the cable headend 208 and the set top terminal 220. This connection is possible through the local telephone, cellular telephone or a personal communications network (PCN).

[0101] The basic programming of each set top terminal 220 is located on ROM within the set top terminal 220. Random access memory, the magnetic cartridge capability, and the expansion card slot 635 each allow upgrades and changes to be easily made to the set top terminal 220.

[0102] In the preferred embodiment, the set top terminal 220 includes a hardware upgrade port 662. In addition to expansion card slots. The hardware upgrade port 662 accommodates a four-wire (or more) connection for: (1) error corrected, decrypted data output of the set top terminal 220, (2) a control interface, (3) decompressed video output, and (4) a video input port. In the preferred embodiment, multiple wires are used to perform each of the four functions. The four sets of wires are combined in a single cable with a single multipin connector.

[0103] In the preferred embodiment, multipin connections may be used for the multiwire cable. The multipin connection 662 may range from DB9 to DB25. A variety of small computer systems interface (SCSI) ports may also be provided. Alternatively, four or more ports may be provided instead of the single port depicted.

[0104] Another port 662 is used to attach the various hardware upgrades described below to a set top terminal 220. The preferred embodiment has a number of hardware upgrades available for use with a set top terminal 220, including: (1) a Level A interactive unit, (2) a Level B interactive unit, (3) a Level C interactive unit with compact disc capability, (4) a Level D digital radio tuner for separate room use, and (5) a Level E information download unit. Each of these upgrades may be connected to the set top terminal 220 unit through the upgrade port 662 described earlier. The same four wires in a single cable described earlier may be used.

[0105] Existing set top converter boxes such as those made by Scientific Atlanta or General Instruments are presently unequipped to handle the menu selection system of the present invention. Thus, hardware modifications are necessary in order to use the menu selection system with existing set top converter technology.

[0106] A Turbo Card addition to a set top converter is depicted in Figure 6. The Turbo Card 700 shown provides the additional functionality needed to utilize the menu system with existing set top converter technology. The primary functions the Turbo Card 700 adds to the set top converter are the interpreting of program control information signals, generating of menus, sequencing of menus, and, ultimately, the ability of the viewer to select a channel through the menu system without entering any channel identifying information. The turbo card also provides a method for a remote location, such as the cable headend 208, to receive information on programs watched and control the operation of the set top converter and Turbo Card 700. The programs watched information and control commands may be passed from the cable headend 208 to the Turbo Card 700 using telephone lines.

[0107] The primary components of the Turbo Card 700 are a PC chip CPU 702, a VGA graphic controller 704, a video combiner 706, logic circuitry 708, NTSC encoder 710, a receiver 712, demodulator 714, and a dialer 716. The Turbo Card 700 operates by receiving the program control information signal from the cable headend 208 through the coaxial cable. The logic circuitry 708 of the Turbo Card 700 receives data, infrared commands, and synchronization signals from the set top converter. Menu selections made by the viewer on the remote control 900 are received by the set top converter's IR equipment and passed through to the Turbo Card 700. The Turbo Card 700 interprets the IR signal and determines the program (or menu) the viewer has selected. The Turbo Card 700 modifies the IR command to send the program selection information to the set top converter 221. The modified IR command contains the channel information needed by the set top converter. Using the phone line and dialer 716, the Turbo Card 700 is able to transmit program access information to the cable headend 208.

[0108] In the preferred embodiment, program access information is stored at each set top terminal 220 until it is polled by the network controller 214 using a polling request message format as shown in Figure 7a. This frame format 920 consists of six fields, namely: (1) a leading flag 922 at the beginning of the message, (2) an address field 924, (3) a subscriber region designation 926, (4) a set top terminal identifier 928 that includes a polling command/response (or P/F) bit 930, (5) an information field 932, and (6) a trailing flag 934 at the end of the message. Figure 7b shows a response frame format 920' (similar to the frame format 920 end, therefore, commonly numbered with the frame depicted in Figure 7a, but with the prime indicator added for clarity) for information communicated by the set top terminal 220 to the network controller 214 in response to the polling request of Figure 7a.

[0109] The eight-bit flag sequence 922 that appears at the beginning and end of a frame is used to establish and maintain synchronization. Such a sequence typically consists of a "01111110" bit-stream. The address field 924 designates a 4-bit address for a given set top terminal 220. The subscriber region designation 926 is a 4-bit field that indicates the geographical region in which the subscriber's set top terminal 220 is housed. The set top terminal identifier 928 is a 16-bit field that uniquely identifies each set top terminal 220 with a 15-bit designation followed by an appended P/F bit 930. Although field size is provided by this example, a variety of sizes can be used with the present invention.

[0110] The P/F bit 930 is used to command a polling response from the set top terminal 220 addressed, as described below. The response frame format 920' also provides a variable-length information field 932' for other data transmis-

sions, such as information on system updates. The frame format 920' ends with an 8-bit flag (or trailing flag) 934' that is identical in format to the leading flag 922', as set forth above. Other frame formats (e.g., MPEG) will be apparent to one skilled in the art and can be easily adapted for use with the system.

[0111] As summarized above, images or programs may be selected for display by sequencing through a series of menus. Figure 8 is an example of one possible structure for a series of menus. Generally, the sequence of menus is structured with an introductory menu, a home menu, various major menus and a multitude of submenus. The submenus can include promo menus and during program menus. For example, at the home menu portion of the sequence of menus and corresponding software routines, a subscriber may select one of the major menus and start a sequence of menu displays. Alternatively, a subscriber may go directly to a major menu by depressing a menu select button on remote control 900.

[0112] At any time during the menu sequence, the subscriber may depress a major menu button to move into another series of menus. In this way, a subscriber may move from major menu to major menu.

[0113] The various software subroutines executed by the microprocessor 602 allow a subscriber to sequence the menus, navigating through the various menus of the present invention. A subscriber may sequence back through menus or return to the home menu with a single touch of the home menu button on remote 900.

[0114] An introductory menu screen 1000 automatically appears upon power-up and initialization of the set top terminal 220. From this introductory menu screen 1000, the set top terminal software will normally advance the subscriber to the home menu screen 1010. The home menu 1010 is the basic menu that the subscriber will return to in order to make the first level of viewing decisions. When the set top terminal software is displaying the home menu 1010, the subscriber is able to access any television programming option. The software allows programming options to be entered through cursor movement on the screen and directly by button selection on the remote control 900.

[0115] In the normal progression through the menu screens, the software will forward the subscriber to a major menu screen 1020 in response to the subscriber's remote control 900 selection or highlighted cursor selection from the home menu screen 1010. The selections displayed on the home menu 1010 are for large categories of programming options.

[0116] Following the major menu 1020, the subscriber may navigate through one or more submenu screens 1050 from which the subscriber may choose one particular program for viewing. For most programming selections, the user will proceed from the home menu 1010 to a major menu 1020 and then to one or more submenus 1050. However, for certain programming options or functions of the set top terminal 220, the user may skip one or more menus in the sequence.

[0117] The During Program Menus 1200 are submenus enabled by the set top terminal software only after the subscriber has selected a television program. These menus provide the subscriber with additional functionality and/or additional information while viewing a selected program. The During Program Menus 1200 sequence can be further subdivided into at least two types of menus, Hidden Menus 1380 and Program Overlay Menus 1390.

[0118] To avoid disturbing a subscriber during viewing of a program, the Hidden Menus 1380 are not shown to the subscriber but instead "reside" at the set top terminal 220 microprocessor 602. The microprocessor 602 awaits a button entry either from the remote control 900 or set top terminal 220 buttons before executing or displaying any Hidden Menu 1380 options. The set top terminal software provides the subscriber with additional functions such as entering an interactive mode or escaping from a selected program through use of Hidden Menus 1380.

[0119] Program Overlay Menus 1390 are similar to Hidden Menus 1380. However, the Program Overlay Menus 1390 are overlaid onto portions of the displayed video and not hidden. The software for the Program Overlay Menus 1390 allows the subscriber to continue to watch the selected television program with audio but places graphical information on a portion of the television screen. Most Program Overlay Menus 1390 are graphically generated to cover small portions of video. Some Overlays 1390 which are by their nature more important than the program being viewed will overlay onto greater portions of the video. Examples of types of overlay menus 1390 include Notification Menus 1392 and Confirmation Menus 1394. In the preferred embodiment, the software for the Program Overlay Menus 1390 controls the reduction or scales down the (entire) programs video and redirects the video to a portion of the screen.

[0120] Submenus provide the cost of viewing the program and the program's length in hours and minutes. From the submenus, the subscriber is given at least three options: (1) to purchase a program, (2) to return to the previous menu, and (3) to press "go" and return to regular TV. The subscriber may also be given other options such as previewing the program.

[0121] Using an on-screen menu approach to program selection, there is nearly an unlimited number of menus that can be shown to the subscriber. The memory capability of the set top terminal 220 and the quantity of information that is sent using the program control information signal are the only limits on the number of menus and amount of information that can be displayed to the subscriber. The approach of using a series of menus in a simple tree sequence is both easy for the subscriber to use and simply implemented by the set top terminal 220 and remote control device 900 with cursor movement. A user interface software programmer will find many obvious variations from the preferred embodiment described.

[0122] The set top terminal 220 generates and creates menus using, in part, information stored in its graphics mem-

ory. A background graphics file 800 will store menu backgrounds and a logo graphics file will store any necessary logos. A menu display and cursor graphics file will store menu display blocks and cursor highlight overlays as well as any other miscellaneous files needed to build the menus. Using this method of storing menus, the menus can be changed by reprogramming the graphics memory of the set top terminal 220 through instructions from either the network controller 214 or operations center 202.

[0123] The microprocessor 602 performs the steps required to create a menu using stored information. The microprocessor 602 fetches a background file, logo file, menu display and cursor file in most instances. The microprocessor 602 fetches text from long-term, intermediate-term, or short-term storage depending on where the text is stored. Using a video combiner (or like device), the stored information is combined with video and the entire image is sent to the television screen for display.

[0124] In the preferred embodiment, a graphics controller is used to assist the set top terminal 220 in generating menus. Menu generation by the set top terminal 220 begins with the building of a major menu screen, which includes background graphics for that major menu. The background graphics may include an upper sash across the top of the screen and a lower sash across the bottom of the screen. The background graphics may be generated from the background graphics file 800 in the memory files of the graphics memory (preferably EEPROM). In addition, logo graphics may be generated. Such graphics typically include an icon window, a cable company logo, a channel company logo, and two "go" buttons.

[0125] Preferably, the text for each major menu is generated separately by a text generator in the set top terminal 220. Those portions of the text that generally remain the same for a period of weeks or months may be stored in EEPROM or other local storage. Text which changes on a regular basis, such as the movie titles (or other program selections), is transmitted to the set top terminal 220 by either the operations center 202 or the network controller 214 of the cable headend 208. In this manner, the cable headend 208 may change the program selections available on any major menu 1020 by modifying the program control information signal sent by the operations center 202 and transmitting any changes using the STTCIS.

[0126] Day, date and time information are added to each major menu. This information is sent from the operations center 202, the cable headend 208 (signal processor 209 or network controller 214), the uplink site, or generated by the set top terminal 220 internally.

[0127] The creation and display of program description submenus is performed by the set top terminal 220 in a manner similar to that described above. Each submenu may be created in parts and combined before being sent to the television screen. Preferably, background graphics and upper and lower sashes are used. Likewise, a video window and half-strip window can be generated from information in storage on the EEPROM.

[0128] In addition to graphics and text, some submenus include windows that show video. Such video may be still or moving pictures. Still pictures may be stored in a compressed format (such as JPEG) at the set top terminal 220. Video stills may be transmitted by the operations center 202 through the program control information signal from time to time.

[0129] Moving video picture is obtained directly from a current video feed as described above. Depending on video window size, this may require manipulation of the video signal, including scaling down the size of the video and redirecting the video to the portion of the menu screen which is within the video window of the menu. Alternatively, the video may be obtained from a split screen channel. Such a method involves the use of split screen video techniques to send multiple video clips on a single channel at a given time. The set top terminal 220 would scale the picture, if necessary, and redirect it to the correct position on the screen using known scaling and positioning techniques. Additional circuitry may be required in the set top terminal 220 to perform adequate scaling and repositioning.

[0130] To avoid the need for redirecting video into the portion of the screen which houses the video window, masking and menu graphics may be used to cover the portions of the channel video that are not needed. This masking technique allows the split screen video to remain in the same portion of the screen that it is transmitted by the operations center 202. The masking is then adjusted to cover the undesired portions of the screen. These masks are stored in the background graphics file similarly to other background files for menus.

[0131] The split screen video technique may also be used for promoting television programming. Since a great number of short video clips may be sent continuously, full or partial screen promotionals (or informationals) may be provided to the subscriber. With this large quantity of promotional video, the subscriber is given the opportunity to "graze" through new movie or television programming selections. The subscriber simply grazes from promotional video to promotional video until the desired television program is discovered.

C. Program Control Information Signal

[0132] Throughout the present application, the term "program control information" is being used to indicate control information coming from the cable headend 208 to the set top terminal 220, whether it is sent directly from the Operations Center 202, processed by the network controller 214 and then forwarded to the set top box, or transmitted over

telephone lines.

[0133] The program control information signal generated by the Operations Center 202 provides data on the scheduling and description of programs to the network controller 214 or, in an alternate configuration, directly to the set top terminal 220 for display to the subscriber. In the preferred embodiment, the program control information signal is stored and modified by the network controller 214 and sent to the set top terminal 220 in the form of a set top terminal control information stream (STTCIS). This configuration is required to accommodate differences in individual cable systems and possible differences in set top terminal devices. The set top terminal 220 integrates either the program control information signal or the set top terminal control information stream together with data stored in the memory of the set top terminal 220, to generate on-screen displays for assisting the subscriber in choosing programs.

[0134] The goal of the menu driven program selection system 200 is to allow the subscriber to choose a program by touring through a series of menus, organized generally as depicted in Figure 8, utilizing the remote control 900 for cursor movement. The final choice in the series of menus will identify one particular channel and one time for activation of that channel. Armed with a channel and activation time the set top terminal 220 can display the selected program on the television for the viewer. To achieve this goal a simple embodiment assigns an intelligent alpha-numeric code to each program. This alpha-numeric code identifies the category of the program, the menu in which the program should be displayed, its transmission time(s), and the position on the menu that the program should be displayed.

[0135] In this simple embodiment, the program control information, including menu codes, is sent continuously from the Operations Center 202 to the network controller 214, and ultimately to the set top terminal 220. For example, four hours worth of programming information can be sent via the program control information signal continuously as shown in Table A.

[0136] Table A shows the basic programming information that may be sent to the set top terminal 220. The program descriptions shown are coded abbreviations. For example, C for comedy, N for news, S for sports, A for cartoons, and Tx for text. If there is a textual description for a program, such as a movie, the description may be given following that program's coded description or may be communicated following the four hours' worth of programming information. As is shown in the coded listing, program descriptions for programs greater than a half hour in length need not be repeated (each half hour). The video description code informs the set top terminal 220 of whether there is still or live video available to advertise the program.

[0137] For example, a sporting program may be assigned a code of B35-010194-1600-3.25-Michigan St. vs. USC. The letter B would assign the program to category B, sports. The second alpha-numeric character number 3 would assign the program to the third menu of the sports category. The third character of the code, number 5, assigns the program to the fifth program slot on the third menu. The next six characters, 01/01/94, represent the date. The following four characters, 1600 represent the start time which is followed by the length of the program and the program name. This entry represents a sports show, a college football game, which will be aired at 4:00PM on New Years day 1994.

TABLE A

12 PM					
	*Program name	*Program length	*Menu code	*Description	*Video
1	Cheers	.5	E24	C	N
2	Terminator	2.0	A33	Tx	S
3	Prime Time	1.0	D14	N	N
4	Football Special	.5	B24	S	N
•					
•					
•					
•					
12:30 PM					
	*Program name	*Program length	*Menu code	*Description	*Video
1	Simpsons	.5	E14 & C13	C	S
4	Football Game	3.0	B13	S	N
•					

TABLE A (continued)

12:30 PM					
*Program name		*Program length	*Menu code	*Description	*Video
•					
•					

[0138] In the 12:30 Channel 1 entry of Table A, two menu codes are shown. By allowing two menu codes, programs that may fit under two different category descriptions may be shown in both menus to the subscriber. With this minimal amount of information being communicated to the set top terminal 220 on a regular basis, the terminal is able to determine the proper menu location for each program and the proper time and channel to activate for the subscriber after his menu selection.

[0139] Table B shows an example Events Table that may be downloaded to a set top terminal 220 using the Event.Dat file which contains information about events and pricing. As shown in the table, the three columns of the Events Table identify the field number, the field itself and the type of information downloaded in the Event.Dat file. The first column contains the field numbers 1 through 11. The middle column contains the corresponding field parameters, including the event type, event ID, global channel ID, price, start time, end time, start date, end date, P- icon, name and description. The third column contains corresponding field type information. Field type information typically consists of an unsigned integer: hours, minutes and seconds; months, day and year: and ASCII character identifier.

TABLE B

Field #	Field	Type
1	Event Type 1 = YCTV 2 = Pay-Per-View 3 = Reg. TV	Unsigned Int
2	Event ID	Unsigned Int
3	Global Channel ID	Unsigned Int
4	Price (in Cents)	Unsigned Int
5	Start Time	HH:MM:SS
6	End Time	HH:MM:SS
7	Start Date	MM/DD/YY
8	End Date	MM/DD/YY
9	P-Icon	ASCIIZ
10	Name	ASCIIZ
11	Description	ASCIIZ

[0140] Table C shows an example Event.Dat data file. In particular, Table C shows two data streams corresponding to two event types. The first data stream identifies a YCTV™ event in the first field. The second field designates the event ID, which is 1234 in this example. The third field includes the global channel ID number two. The fourth field indicates the cost of 50 cents for this event. The fifth and sixth fields indicate the respective start and end times of 3:00 AM to 3:00 PM, respectively. The seventh and eighth fields show the corresponding start and end dates, designated as 8/25/93 and 8/27/93, respectively. Field nine indicates the P-icon set to PBS.PCX graphics file. Finally, fields ten and eleven indicate the name and description of the events selected, which in this case are Sesame Street™ and Barney™. The second data stream in the Event.Dat example shown in Table C includes analogous information for Terminator IV™, which is designated in field one as a pay-per-view event.

TABLE C

Event.Dat Example

1	1234	2	50	03:00:00	15:00:00	08/25/93	08/27/93	pba.pcx	Sesame Street & Barney's Sesame Street and Barney Abstract
2	1234	2	50	20:00:00	22:00:00	08/25/93	08/25/93	14.pcx	Terminator 4 Terminator 4 Abstract

[0141] The program control information signal and STTCIS can be formatted in a variety of ways and the on-screen menus can be produced in many different ways. For instance, if the program control information signal carries no menu format information, the menu format for creating the menus can be fixed in ROM at the set top terminal. This method allows the program control information signal to carry less information but has the least flexibility since the menu formats can not be changed without physically swapping the ROM.

[0142] In the preferred embodiment, the menu format information is stored at the set top terminal 220 in temporary memory either in a RAM, FLASH ROM, EEPROM or EPROM. This configuration provides the desired flexibility in the menu format while still limiting the amount of information needed to be communicated via the program control information signal. New menu format information can be sent via the program control information signal or the STTCIS to the set top terminals 220 each time there is a change to a menu.

[0143] Program access information for each program watched is stored at the set top terminal 220 until it is polled by the network controller 214 for information retrieval using the program control information signal or STTCIS. This information retrieval can be accomplished by using the polling request message and response formats, 920 and 920' respectively, as shown, and Figures 7a and 7b, and described above, but any suitable polling request and response message format may be used to interrogate each set top terminal 220 sequentially, one by one. The set top terminals 220 are identified by a unique address and set top terminal identifier. It is preferred that the set top terminal 220 transmit information and messages to the network controller 214 only when given permission by the network controller 214 to do so.

[0144] Where, for example, specialty programs have been accessed since the previous poll, the set top terminal 220 is given permission to transmit a polling response 920' in the form of a status report that includes any such access information. The network controller's control receiver (not shown) is tasked with the receipt of set top terminal polling responses or status reports. These status reports generally include information that allows the network controller 214 to track a subscriber's program access history.

[0145] Figure 7b shows an example of frame format 920' for the status reports received from the set top terminals 220 during the polling cycle. This frame format is identical to the polling request message format 920 and, as described, includes: (1) a leading flag 922' at the beginning of the message, (2) an address field 924', (3) a subscriber region designation 926', (4) a set top terminal identifier 928' that includes a polling command/response (or P/F) bit 930', (5) an information field 932', and (6) a trailing flag 934' at the end of the message.

[0146] The information field 932' remains variable in length so that the status of an indeterminate number of programs, represented at 931, accessed can be included in the frame. In this way, the control message length of the polling request message is minimal since the network controller 214 does not transmit such access information. After a polling response by a given set top terminal 220, however, the control message length increases in proportion to the number of programs accessed.

[0147] During transmission, the P/F bit is used to carry out the polling function. In particular, the P/F bit is set to a "1" position to command a polling response from the set top terminal 220 whose address is identified in the frame. The set top terminal 220 addressed must respond to the command in the same P/F bit also set to the "1" position. The response will include the number of programs accessed and their corresponding event identification numbers as shown in Figure 7b at 931. In cases where the set top terminal 220 has not accessed any programs since the previous polling cycle, the set top terminal 220 responds with the P/F bit set to "1" and the programs access block denoting zero programs accessed.

[0148] In between polling cycles, the program control information continues to supply the set top terminals 220 with menu information. In the simplest embodiment, the menus remain fixed and only the text changes. Thus, the program control information signal can be limited to primarily text and a text generator can be employed in the set top terminal 220. This simple embodiment keeps the cost of the set top terminal 220 low and limits the bandwidth necessary for the program control information. Another simple embodiment uses a separate channel full-time (large bandwidth) just for the menu information. This separate channel would facilitate the rapid downloading of new graphics for the system and would enhance response time when text and other data information needs to be changed.

[0149] In the preferred embodiment, the basic building blocks or templates of the on-screen menu displays will be stored in graphics memory consisting of nonvolatile RAM, FLASH ROM, EPROM, or preferably, EEPROM, as shown

as 620 in Figure 9a. Referring to Figure 4, with the information from the graphics memory 620, the microprocessor 602, graphics decompressor 622; a text generator (not shown in Figure 4, but incorporated if necessary), and video combiner 624 will build a menu screen.

[0150] The memory files of the graphics memory are preferably categorized into three categories, background graphics 800, logo graphics 820, and menu and display graphics 850, as shown in Figure 9a.

[0151] The background graphics file 800 will store menu backgrounds such as: universal main menu backgrounds 804, universal submenu backgrounds 808, promo backgrounds 812 and custom menu formats 816. The logo graphics file 820 will store any necessary logos such as: Your Choice TV™ logos 824. Network logo files 828, cable system logo files 832, studio logo files 836, and graphic elements file 840. The menu display and cursor graphics file 850 will store menu display blocks 854 and cursor highlight overlays 858, as well as any other miscellaneous files needed to build the menus.

[0152] Using this method of storing menus discussed above, the menus can be changed by reprogramming the graphics memory 620 of the set top terminal 220. To revise the entire design of displayed menus, the network controller 214 or operations center 202 instructs the EEPROM 620 to be erased and reprogrammed with new menu templates. To change one menu format or logo, the network controller 214 or operations center 202 instructs just the one location in memory to be erased and rewritten. Obviously, this menu reprogramming can also be done locally (at the set top terminal 220) by a servicemen.

[0153] As shown in Figure 9a, each memory subfile is further divided into various memory blocks. For example, the background graphics file 800 contains the universal main menu backgrounds 804. The universal main menu backgrounds memory 804 includes memory units UM1 860, UM2 862 and UM3 863. Similarly, the logo graphics file 820 and menu display and cursor graphics file 850 contain individual subfile memory blocks (for example, studio logo file 836 has memory block SL1 864; menu display blocks 854 has memory menu display block MD1 866).

[0154] Figure 9b shows the hierarchical storage of text transmitted from the cable headend 208. Although text may be continuously transmitted with the video signals to set top terminals 220, text may also be transmitted intermittently. In such a case, the text is stored in the set top terminal 220. Preferably, the text is transmitted and stored in a compressed format using known techniques. Additionally, the text is preferably stored in graphics memory 620 within the set top terminal 220.

[0155] Depending upon the use of the text it will be stored in one of three portions of memory. Information sent with the text will either direct the text to a particular portion of memory, or include information as to the priority of text. The microprocessor 602, part of the set top terminal hardware represented at block 880, may then direct the text to the appropriate memory location for storage.

[0156] If the text is to be used frequently and over a long period of time a long term storage 875 will be used. If the text will be used for a shorter period of time (for example, a month), the text will be directed to an intermediate storage area 877. If the text is to be used almost immediately, or for a short period of time (for example, within a few days) the text is directed to a short term storage area 879. The microprocessor 602 locates the appropriate text required for a particular menu and retrieves it from the appropriate portion of memory 620. The text is output from the graphics memory 620 to the text generator 621. Text generated from the text generator 621 is thereafter directed to text/graphics video combiner 624.

[0157] Figure 9c shows the steps performed by the microprocessor 602 for creating a menu based upon a series of overlay screens. These instructions are stored in memory within the set top terminal 220 in a screens data file. The screens data file instructs the microprocessor 602 on the location of each graphics file on the screen. An example screens data file is shown in Table D, wherein the screens data file specifies menu data positioning in terms of, for example, x and y pixel positions, height and width, color codes and fonts. Alternatively, instructions or routines may be transmitted from the operations center 202 to be stored in memory within the individual set top terminals 220.

TABLE D

~ The following data lines are for the main menu												
~												
~	Screen Type				Template File			Description				
SCREEN	`@MAIN				`main menu.pcx			`Main Menu				
~												
~	Justify	X	Y		Ht	Wd	FColor	BColor	Font			
STR POS	`Left	`165	`85		`30	`300	`27	`55	FUTUR14.GFT			
STRING `MAIN MENU												
~												
~	Justify	X	Y		Hght	Wdt						
PCX POS	`LEFT	`190	`75		`200	`200						
PCX example.pcs												
~												
~	Justify	X	Y	Ht	Wd	FColor	BColor	Font	X	Y	Ht	Wd
ITEM POS	`Left	`120	`100	`20	`400	`15	`25	FUTUR12.GFT	`110	`90	`30	`420
ITEM`@YCTV`YOUR CHOICE TV												
~												
~	Justify	X	Y	Ht	Wd	FColor	BColor	Font	X	Y	Ht	Wd
ITEM POS	`Left	`120	`200	`20	`400	`15	`25	FUTUR12.GFT	`110	`190	`30	`420
ITEM `@PPV`PAY-PER-VIEW HIT MOVIES												

[0158] As shown at block 878 in Figure 9c, initially the microprocessor 602 instructs the tuner 603 to select a channel. The channel is decompressed, error corrected and decrypted, if necessary. If the video is to be reduced in size, so as to be placed within a video window, or is a split screen video window which must be enlarged, the video is scaled to the appropriate size. Additionally, the video may be required to be redirected to a portion of the television screen, accomplished by creating a series of offsets for each pixel location of the video.

[0159] Graphics must also be used to create a menu in most instances. As shown in block 882, the microprocessor 602 must fetch a background file, a logo file, and a menu display and cursor file in most instances. Each of these files is decompressed 883, and then combined, block 886.

[0160] Similarly, the microprocessor 602 must fetch text, as shown in block 884. Depending upon the memory location of the text, the microprocessor 602 will fetch the text from long-term, intermediate-term, or short-term storage, as described above. Based upon this memory retrieval, the text is generated, block 885, and combined with the video (if any), with as many screens of a decompressed graphics as are necessary, and any text, block 886. The image or portions of the image are stored in the video combiner (for example, combiner 624 of Figure 4) until all overlays are received. Thereafter, the entire image is sent, under direction of another routine, to be displayed on the television screen, as represented by display block 888.

Claims

1. A system for delivering digital program signals from a center (202) to subscriber locations using a first satellite (206) with a first satellite transponder, the system comprising:

a center (202), remotely located from the subscriber locations, wherein more than one digital program signal is processed for transmission to the first satellite transponder, wherein the digital program signals are packaged and provided with a program control information signal before said transmission;
a first cable headend (208) comprising:

a first satellite dish, wherein the digital program signals are received from the first satellite transponder; and
means (214), connected to the first satellite dish, for sending the digital program signals from the first cable headend (208) to the subscriber locations, and

a first terminal (220), located at each subscriber location, wherein the sent digital program signals are received from the first cable headend (208) and at least one digital program signal is processed for subscriber viewing.

2. The system of claim 1, wherein the center (202) packages at least one digital program signal for transmission to the first cable headend (208), and wherein the first cable headend (208) further comprises a processor (209), connected to the first satellite dish and the sending means (214), wherein the received package of digital program signals are screened and at least one digital program signal is separated from the received package of digital program signals.

3. The system of claims 1 or 2, wherein the first cable headend (208) comprises:

a processor (209), operably connected to the first satellite dish, wherein the received digital program signals are processed to form a set of screened digital program signals, and wherein the screened digital program signals are a subset of the received digital program signals; and
means (214), operably connected to the processor (209), for sending the subset of screened digital program signals from the processor (209) to subscriber locations.

4. The system of claims 2 or 3, wherein the first terminal (220) further comprises an input port (652), wherein the screened digital program signals are received by the first terminal (220).

5. The system of any of claims 2 to 4, wherein local program signals are used at the first cable headend (208), the first cable headend (208) further comprising a signal processor (209), operably connected to the first satellite dish and the sending means (214), wherein local program signals may be inserted into the packaged digital program signals.

6. The system of any of claims 1 to 5, wherein the center (202) further comprises a computer, wherein the computer sends directions to the first cable headend (208), along with the digital program signals, which enable the signal

processor (209) to control insertion of local program signals at the first cable headend (208).

7. The system of claim 6, wherein a port at the first terminal (220) receives the screened digital program signals and the local program signals inserted by the signal processor (209).

8. The system of any of claims 1 to 7, wherein the system further comprises a second satellite transponder and a second cable headend, the first and second transponders being used to transpond a first and second group of digital program signals to the cable headends, the center (202) further comprising a processor (209), wherein the first and second groups of digital program signals are allocated for transmission to the first or second satellite transponder, and wherein each satellite transponder receives a different group of digital program signals.

9. The system of claim 8, wherein the center (202) further comprises:

a first transmitter, wherein the first group of digital program signals are transmitted to the first satellite transponder, and wherein the first cable headend (208) receives digital program signals from the first satellite transponder; and

a second transmitter, wherein the second group of digital program signals are transmitted to the second satellite transponder, and the second cable headend receives digital program signals from the second satellite transponder.

10. The system of any of claims 1 to 9, wherein the digital program signals are comprised of both audio and video signals, and more than one audio channel may exist for a video signal, wherein the first satellite dish at the first cable headend (208) receives the video and audio signals from the first satellite transponder, and wherein a particular video signal may have multiple audio channels associated therewith, the first cable headend (208) further comprising a controller, wherein the controller selects one or more received audio channels to correspond to the particular video signal, wherein a listener receives at least one selected audio channel.

11. The system of claim 10, wherein more than one language is represented in the multiple audio channels associated with the particular video signal, and wherein the first cable headend (208) receives information from subscriber locations, the controller at the first cable headend (208) further comprising means for selecting a particular audio channel in response to information received from the subscriber location.

12. The system of claim 11, wherein the first terminal (220) further comprises:

means (640) for displaying menus of language options to the subscriber; and
an interface (626), wherein menu selections entered by the subscriber are received, and
wherein the information received at the first cable headend (208) from the subscriber location includes the menu selection made by the subscriber in response to the menu displaying language options using the interface (626).

13. The system of any of claims 1 to 12, wherein a second satellite is used, the first cable headend (208) further comprising a second satellite dish, wherein the second satellite dish receives digital program signals from a second satellite transponder.

14. The system of any of claims 1 to 13, wherein a first and second groups of terminals are serviced by the first cable headend (208), the first group of terminals receiving digital program signals from the first satellite transponder through the first satellite dish, and the second group of terminals receiving digital program signals from a second satellite transponder through a second satellite dish, and wherein at least one of the digital program signals received from the first satellite transponder is different from the digital program signals received from the second satellite transponder.

15. The system of any of claims 2 to 14, wherein the digital program signals contain more than one digital audio/video program, the processor (209) in the first cable headend (208) comprising means for separating individual digital audio/video programs from the digital program signals received from the first satellite transponder by the first satellite dish.

16. A system for delivering digital program signals from a center (202) to subscriber locations using a satellite (206) with satellite transponders, wherein the digital program signals are sent to the subscriber locations through a

satellite system, the system comprising:

a center (202), remotely located from the subscriber locations, wherein more than one digital program signal is processed for transmission to a first satellite transponder, wherein the digital program signals are packaged and provided with a program control information signal before said transmission;
a first satellite dish, located at a first subscriber location, wherein the digital program signals are received from the first satellite transponder; and
a first terminal (220), located at the first subscriber location, and connected to the first satellite dish, wherein the digital program signals are received and at least one digital program signal is processed for subscriber viewing.

17. The system of claim 16, wherein the system further comprises a second satellite transponder and a second terminal, the first and second transponders being used to transpond a first and second group of digital program signals to the terminals, the center (202) further comprising a processor (209), wherein the first and second groups of digital program signals are allocated for transmission to the first or second satellite transponder, and wherein each satellite transponder receives a different group of digital program signals.

18. The system of claim 17, wherein the center (202) further comprises:

a first transmitter, wherein the first group of digital program signals are transmitted to the first satellite transponder, and wherein the first terminal (220) receives digital program signals from the first satellite transponder through the first satellite dish; and
a second transmitter, wherein the second group of digital program signals are transmitted to the second satellite transponder, and the second terminal receives digital program signals from the second satellite transponder through the second satellite dish.

19. The system of any of claims 1 to 18, wherein the center (202) further comprises a processor (209), wherein a program control information signal is generated, which is used by the first terminal (220).

20. The system of any of claims 1 to 19, wherein a program control information signal is packaged with the digital program signals.

21. The system of claims 19 or 20, wherein the first terminal (220) further comprises means for generating menu displays using the program control information signal.

22. The system of any of claims 19 to 21, wherein the program control information signal includes data on program titles.

23. The system of any of claims 19 to 22, wherein the program control information signal includes data on program start times.

24. The system of any of claims 19 to 23, wherein the program control information signal includes data on menus.

25. The system of any of claims 19 to 24, wherein the program control information signal includes data on program line-ups for more than one channel of programming.

26. The system of any of claims 1 to 25, wherein the center (202) further comprises a compressor, wherein the digital program signals are compressed prior to transmission to the first satellite transponder.

27. The system of any of claims 1 to 26, wherein the first terminal (220) includes a decompressor (618), wherein the received digital program signals are decompressed for display to the subscriber.

28. The apparatus of any of claims 1 to 27, wherein the first terminal (220) comprises a digital set top terminal, wherein the digital set top terminal is used at the subscriber location, and wherein the digital set top terminal decompresses the sent digital program signals.

29. The system of any of claims 1 to 28, wherein the first terminal (220) comprises a set top terminal, and wherein the set top terminal is operably connected to a television (222).

30. The system of any of claims 1 to 29, wherein the first terminal (220) comprises an electronic insertable card (700).
31. The system of any of claims 1 to 30, wherein the first terminal (220) further comprises a processor (602), wherein the digital program signals are converted into analog program signals for display at the subscriber location
32. The system of any of claims 1 to 31, wherein the digital program signals are comprised of digital audio signals, the first terminal (220) comprising:
- means (603) for receiving the digital audio signals; and
- means (612) for outputting the digital audio signals to a listener.
33. The system of claim 32, wherein the system further comprises a third terminal, connected to the first terminal (220), and located remotely from the first terminal (220), wherein the digital audio signals are received and output to the listener.
34. The system of claim 33, wherein the third terminal outputs digital audio signals, and the first terminal (220) concurrently outputs digital audio and video signals for subscriber viewing.
35. The system of any of claims 1 to 34, wherein the center (202) comprises a receiver which receives the digital program signals from an external program source.
36. The system of any of claims 1 to 35, wherein the center (202) is capable of converting analog signals received from an external program source into digital signals before sending the digital program signals from the center (202) to the subscriber locations, the center (202) further comprising:
- a receiver, wherein analog signals are received from external program sources; and
- a converter, wherein the received analog signals are converted into digital program signals.
37. The system of any of claims 1 to 36, wherein the center (202) further comprises a processor (209), wherein the digital program signals are packaged for transmission to the first satellite transponder, and wherein the packages include at least one digital program signal.
38. The system of any of claims 1 to 37, wherein the center (202) acts as a master center, the system further comprising a slave center, operably connected to the master center, wherein functions of the slave center are coordinated with the master center.
39. The system of claim 38, wherein the master center controls the functions of the slave center.
40. The system of any of claims 1 to 39, wherein a second satellite dish receives digital program signals from the first satellite transponder.
41. The system of any of claims 1 to 40, the system further comprising an uplink site, operably connected to the center (202), wherein the processed digital program signals are transmitted to the first satellite transponder.
42. The system of claim 41, wherein there is more than one uplink site, and at least one uplink site is located remotely from the center (202).
43. The system of any of claims 1 to 42, further comprising a remote control (900) with a plurality of menu select buttons.

Patentansprüche

1. System zur Abgabe von digitalen Programmsignalen von einer Zentrale (202) an Teilnehmerplätze unter Verwendung eines ersten Satelliten (206) mit einem ersten Satellitentransponder, wobei das System umfaßt:
- eine von den Teilnehmerplätzen entfernt angeordnete Zentrale (202), in der mehr als ein digitales Programmsignal zur Übertragung über den ersten Satellitentransponder verarbeitet wird, wobei die digitalen Programmsignale vor der Übertragung zu Paketen zusammengefaßt und mit einem Programm-Steuerungsinformationssignal

versehen werden,
einen ersten Kabelendkopf (208) mit

einer ersten Satellitenschüssel, an der die digitalen Programmsignale von dem ersten Satellitentransponder empfangen werden, und
einer mit der ersten Satellitenschüssel verbundenen Einrichtung (214) zum Senden der digitalen Programmsignale von dem ersten Kabelendkopf (208) an die Teilnehmerplätze, und

ein an jedem Teilnehmerplatz angeordnetes erstes Endgerät (220), in dem die übertragenen digitalen Programmsignale von dem ersten Kabelendkopf (208) empfangen und mindestens ein digitales Programmsignal zur Betrachtung durch den Teilnehmer verarbeitet wird.

2. System nach Anspruch 1, wobei die Zentrale (202) mindestens ein digitales Programmsignal vor der Übertragung an den ersten Kabelendkopf (208) zu einem Paket zusammenfaßt, und wobei der erste Kabelendkopf (208) einen an die erste Satellitenschüssel und die Sendeinrichtung (214) angeschlossenen Prozessor (209) aufweist, in dem das empfangene Paket von digitalen Programmsignalen funkentstört und aus dem empfangenen Paket mindestens ein digitales Programmsignal separiert wird.

3. System nach Anspruch 1 oder 2, wobei der erste Kabelendkopf (208) aufweist:

einen mit der ersten Satellitenschüssel betriebsmäßig verbundenen Prozessor (209), in dem die empfangenen digitalen Programmsignale zur Bildung einer Gruppe von funkentstörten digitalen Programmsignalen verarbeitet werden, die eine Untergruppe der empfangenen digitalen Programmsignale darstellen, und eine mit dem Prozessor (209) betriebsmäßig verbundene Einrichtung (214) zum Übertragen der Untergruppe von funkentstörten digitalen Programmsignalen von dem Prozessor (209) an die Teilnehmerplätze.

4. System nach Anspruch 2 oder 3, wobei das erste Endgerät (220) ferner einen Eingang (652) aufweist, an dem die funkentstörten digitalen Programmsignale von dem ersten Endgerät (220) empfangen werden.

5. System nach einem der Ansprüche 2 bis 4, wobei an dem ersten Kabelendkopf (208) lokale Programmsignale verwendet werden, wobei der erste Kabelendkopf (208) ferner einen mit der ersten Satellitenschüssel und der Sendeinrichtung (214) betriebsmäßig verbundenen Signalprozessor (209) aufweist, und wobei die lokalen Programmsignale in die zu einem Paket zusammengefaßten digitalen Programmsignale eingefügt werden können.

6. System nach einem der Ansprüche 1 bis 5, wobei die Zentrale (202) ferner einen Computer aufweist, der zusammen mit den digitalen Programmsignalen an den ersten Kabelendkopf (208) Direktiven sendet, die ermöglichen, daß der Signalprozessor (209) die Einfügung von lokalen Programmsignalen an dem ersten Kabelendkopf (208) steuert.

7. System nach Anspruch 6, wobei ein Eingang an dem ersten Endgerät (220) die funkentstörten digitalen Programmsignale und die von dem Signalprozessor (209) eingefügten lokalen Programmsignale empfängt.

8. System nach einem der Ansprüche 1 bis 7 mit ferner einem zweiten Satellitentransponder und einem zweiten Kabelendkopf, wobei der erste und der zweite Transponder dazu dienen, eine erste und eine zweite Gruppe von digitalen Programmsignalen an die Kabelendköpfe zu übertragen, wobei die Zentrale (202) ferner einen Prozessor (209) aufweist, in dem die ersten und die zweiten Gruppen von digitalen Programmsignalen zur Übertragung an den ersten oder den zweiten Satellitentransponder zugeordnet werden, und wobei jeder Satellitentransponder eine andere Gruppe von digitalen Programmsignalen empfängt.

9. System nach Anspruch 8, wobei die Zentrale (202) ferner aufweist:

einen ersten Sender, mit dem die erste Gruppe von digitalen Programmsignalen an den ersten Satellitentransponder übertragen wird, wobei der erste Kabelendkopf (208) die digitalen Programmsignale von dem ersten Satellitentransponder empfängt, und

einen zweiten Sender, mit dem die zweite Gruppe von digitalen Programmsignalen an den zweiten Satellitentransponder übertragen wird, wobei der zweite Kabelendkopf die digitalen Programmsignale von dem zweiten Satellitentransponder empfängt.

10. System nach einem der Ansprüche 1 bis 9, wobei die digitalen Programmsignale aus sowohl Audio- als auch Videosignalen bestehen und für ein Videosignal mehr als ein Audiosignal vorhanden sein kann, wobei die erste Satellitenschüssel an dem ersten Kabelendkopf (208) die Video- und Audiosignale von dem ersten Satellitentransponder empfängt, wobei einem speziellen Videosignal mehrere Audiokanäle zugeordnet sein können, und wobei
5 der erste Kabelendkopf (208) eine Steuerung aufweist, die in Übereinstimmung mit dem speziellen Videosignal ein oder mehrere empfangene Audiokanäle auswählt, wobei ein Zuhörer mindestens einen ausgewählten Audio-kanal empfängt.

11. System nach Anspruch 10, wobei in den dem speziellen Videosignal zugeordneten mehreren Audiokanälen mehr als eine Sprache wiedergegeben ist, wobei der erste Kabelendkopf (208) Informationen von den Teilnehmerplätzen empfängt, und wobei die Steuerung an dem ersten Kabelendkopf (208) ferner eine Einrichtung aufweist, die entsprechend der von dem Teilnehmerplatz empfangenen Information einen bestimmten Audiokanal auswählt.

12. System nach Anspruch 11, wobei das erste Endgerät (220) ferner aufweist:

eine Einrichtung (640), die dem Teilnehmer Sprachoptionsmenüs anzeigt, und
eine Schnittstelle (626), an der von dem Teilnehmer eingegebene Menüwahlen empfangen werden, und
wobei die an dem ersten Kabelendkopf (208) von dem Teilnehmerplatz empfangene Information die Menüwahl
enthält, die der Teilnehmer entsprechend dem Sprachoptionen darstellenden Menü unter Verwendung des
20 Interface (626) trifft.

13. System nach einem der Ansprüche 1 bis 12, wobei mit einem zweiten Satellit gearbeitet wird, und wobei der erste Kabelendkopf (208) ferner eine zweite Satellitenschüssel aufweist, die digitale Programmsignale von einem zweiten Satellitentransponder empfängt.

14. System nach einem der Ansprüche 1 bis 13, wobei von dem ersten Kabelendkopf (208) eine erste und eine zweite Gruppe von Endgeräten bedient werden, wobei die erste Gruppe von Endgeräten digitale Programmsignale von dem ersten Satellitentransponder über die erste Satellitenschüssel und die zweite Gruppe von Endgeräten digitale Programmsignale von einem zweiten Satellitentransponder über eine zweite Satellitenschüssel empfängt, und
30 wobei mindestens eines der von dem ersten Satellitentransponder empfangenen digitalen Programmsignale von dem von dem zweiten Satellitentransponder empfangenen Digitalsignalen verschieden ist.

15. System nach einem der Ansprüche 2 bis 14, wobei die digitalen Programmsignale mehr als ein digitales Audio/Video-Programm enthalten, und wobei der Prozessor (209) in dem ersten Kabelendkopf (208) eine Einrichtung aufweist, die aus den von dem ersten Satellitentransponder über die erste Satellitenschüssel empfangenen digitalen Programmsignalen individuelle digitale Audio/Video-Programme separiert.

16. System zur Abgabe von digitalen Programmsignalen von einer Zentrale (202) an Teilnehmerplätze unter Verwendung eines Satelliten (206) mit Satellitentranspondern, wobei die digitalen Programmsignale über ein Satellitensystem an die Teilnehmerplätze gesendet werden, mit

einer von den Teilnehmerplätzen entfernt angeordneten Zentrale (202), in der mehr als ein digitales Programmsignal zur Übertragung an einen ersten Satellitentransponder verarbeitet wird, wobei die digitalen Programmsignale vor der Übertragung zu Paketen zusammengefaßt und mit einem Programm-Steuerinformationssignal versehen werden,

einer an einem ersten Teilnehmerplatz angeordneten ersten Satellitenschüssel, an der die digitalen Programmsignale von dem ersten Satellitentransponder empfangen werden, und
einem an dem ersten Teilnehmerplatz angeordneten und mit der Satellitenschüssel verbundenen ersten Endgerät (220), in dem die digitalen Programmsignale empfangen werden und mindestens ein digitales Programmsignal zur Betrachtung durch den Teilnehmer verarbeitet wird.

17. System nach Anspruch 16 mit ferner einem zweiten Satellitentransponder und einem zweiten Endgerät, wobei der erste und der zweite Transponder dazu dienen, eine erste und eine zweite Gruppe von digitalen Programmsignalen an die Endgeräte zu übertragen, wobei die Zentrale (202) ferner einen Prozessor (209) aufweist, wobei die erste und die zweite Gruppe von digitalen Programmsignalen zur Übertragung an den ersten oder den zweiten Satellitentransponder zugeordnet sind, und wobei jeder Satellitentransponder eine andere Gruppe von digitalen Programmsignalen empfängt.

18. System nach Anspruch 17, wobei die Zentrale (202) ferner aufweist:

einen ersten Sender, in dem die erste Gruppe von digitalen Programmsignalen an den ersten Satellitentransponder gesendet wird, wobei das erste Endgerät (220) digitale Programmsignale von dem ersten Satellitentransponder über die erste Satellitenschüssel empfängt, und
einen zweiten Sender, in dem die zweite Gruppe von digitalen Programmsignalen an den zweiten Satellitentransponder gesendet wird, wobei das zweite Endgerät digitale Programmsignale von dem zweiten Satellitentransponder über die zweite Satellitenschüssel empfängt.

19. System nach einem der Ansprüche 1 bis 18, wobei die Zentrale (202) ferner einen Prozessor (209) aufweist, in dem ein von dem ersten Endgerät (220) verwendetes Programm-Steuerinformationssignal erzeugt wird.

20. System nach einem der Ansprüche 1 bis 19, wobei ein Programm-Steuerinformationssignal mit den digitalen Programmsignalen zu einem Paket zusammengefaßt wird.

21. System nach Anspruch 19 oder 20, wobei das erste Endgerät (220) ferner eine Einrichtung aufweist, die unter Verwendung des Programm-Steuerinformationssignals Menüanzeigen generiert.

22. System nach einem der Ansprüche 19 bis 21, wobei das Programm-Steuerinformationssignal Daten über Programmtitel enthält.

23. System nach einem der Ansprüche 19 bis 22, wobei das Programm-Steuerinformationssignal Daten über Programm-Anfangszeiten enthält.

24. System nach einem der Ansprüche 19 bis 23, wobei das Programm-Steuerinformationssignal Daten über Menüs enthält.

25. System nach einem der Ansprüche 19 bis 24, wobei das Programm-Steuerinformationssignal Daten über Programmfolgen für mehr als einen Programmkanal enthält.

26. System nach einem der Ansprüche 1 bis 25, wobei die Zentrale (202) ferner einen Prozessor aufweist, in dem die digitalen Programmsignale vor der Übertragung an den ersten Satellitentransponder komprimiert werden.

27. System nach einem der Ansprüche 1 bis 26, wobei das erste Endgerät (220) einen Dekompressor (618) aufweist, in dem die empfangenen digitalen Programmsignale zur Darstellung für den Teilnehmer dekomprimiert werden.

28. System nach einem der Ansprüche 1 bis 27, wobei das erste Endgerät (220) einen digitalen Endgeräteaufsatz aufweist, der an dem Teilnehmerplatz verwendet wird und die gesendeten digitalen Programmsignale dekomprimiert.

29. System nach einem der Ansprüche 1 bis 28, wobei das erste Endgerät (220) einen Endgeräteaufsatz aufweist, der mit einem Fernsehempfänger (222) betriebsmäßig verbunden ist.

30. System nach einem der Ansprüche 1 bis 29, wobei das erste Endgerät (220) eine elektronische Steckkarte (700) aufweist.

31. System nach einem der Ansprüche 1 bis 30, wobei das erste Endgerät (220) ferner einen Prozessor (602) aufweist, in dem die digitalen Programmsignale in analoge Programmsignale zur Darstellung an dem Teilnehmerplatz umgesetzt werden.

32. System nach einem der Ansprüche 1 bis 31, wobei die digitalen Programmsignale aus digitalen Audiosignalen bestehen, und wobei das erste Endgerät (220) aufweist:

eine Einrichtung (603) zum Empfang der digitalen Audiosignale, und
eine Einrichtung (612) zur Ausgabe der digitalen Audiosignale an einen Zuhörer.

33. System nach Anspruch 32, wobei das System ein mit dem ersten Endgerät (220) verbundenes und entfernt von diesem angeordnetes drittes Endgerät aufweist, in dem die digitalen Audiosignale empfangen und an den Zuhörer

ausgegeben werden.

34. System nach Anspruch 33, wobei das dritte Endgerät digitale Audiosignale ausgibt, und wobei das erste Endgerät (220) gleichzeitig digitale Audio- und Videosignale an den Teilnehmer ausgibt.

35. System nach einem der Ansprüche 1 bis 34, wobei die Zentrale (202) einen Empfänger zum Empfang der digitalen Programmsignale von einer externen Programmquelle aufweist.

36. System nach einem der Ansprüche 1 bis 35, wobei die Zentrale (202) so ausgelegt ist, daß sie von einer externen Programmquelle empfangene Analogsignale in Digitalsignale umsetzt, bevor die digitalen Programmsignale von der Zentrale (202) an die Teilnehmerplätze gesendet werden, und wobei die Zentrale (202) ferner aufweist:

einen Empfänger, an dem Analogsignale von externen Programmquellen empfangen werden, und
einen Umsetzer, in dem die empfangenen Analogsignale in digitale Programmsignale umgesetzt werden.

37. System nach einem der Ansprüche 1 bis 36, wobei die Zentrale (202) ferner einen Prozessor (209) aufweist, in dem die digitalen Programmsignale vor der Übertragung an den ersten Satellitentransponder zu Paketen zusammengefaßt werden, die mindestens ein digitales Programmsignal enthalten.

38. System nach einem der Ansprüche 1 bis 37, wobei die Zentrale (202) als Hauptzentrale arbeitet, wobei das System ferner eine mit der Hauptzentrale betriebsmäßig verbundene Unterzentrale aufweist, und wobei Funktionen der Unterzentrale mit der Hauptzentrale koordiniert sind.

39. System nach Anspruch 38, wobei die Hauptzentrale die Funktionen der Unterzentrale steuert.

40. System nach einem der Ansprüche 1 bis 39, wobei eine zweite Satellitenschüssel digitale Programmsignale von dem ersten Satellitentransponder empfängt.

41. System nach einem der Ansprüche 1 bis 40 mit ferner einer mit der Zentrale (202) betriebsmäßig verbundenen Aufwärtsstrecke, über die die verarbeiteten digitalen Programmsignale an dem ersten Satellitentransponder übertragen werden.

42. System nach Anspruch 41, wobei mehr als eine Aufwärtsstrecke vorhanden und mindestens eine davon entfernt von der Zentrale (202) angeordnet ist.

43. System nach einem der Ansprüche 1 bis 42 mit einer Fernsteuerung (900) mit mehreren Menüwähltasten.

Revendications

1. Système pour délivrer des signaux de programmes numériques à partir d'un central (202) auprès de sites abonnés en utilisant un premier satellite (206) avec un premier répéteur-satellite, le système comportant :

un central (202), localisé à distance des sites abonnés, dans lequel plus d'un signal de programmes numériques est traité à des fins de transmission vers le premier répéteur-satellite, les signaux de programmes numériques étant conditionnés et complétés par un signal d'informations de contrôle de programmes avant ladite transmission ;

une première tête de câble (208) comportant :

une première antenne-satellite, par laquelle les signaux de programmes numériques sont reçus à partir du premier répéteur-satellite ; et
des moyens (214), reliés à la première antenne-satellite, pour envoyer les signaux de programmes numériques à partir de la première tête de câble (208) vers les sites abonnés, et

un premier terminal (220), installé dans chaque site abonné, dans lequel les signaux de programmes numériques envoyés sont reçus à partir de la première tête de câble (208) et au moins un signal de programme numérique est traité de manière à permettre à l'abonné de regarder le programme.

2. Système selon la revendication 1, dans lequel le central (202) conditionne au moins un signal de programme numérique à des fins de transmission vers la première tête de câble (208), et dans lequel la première tête de câble (208) comporte en outre un processeur (209), relié à la première antenne-satellite et aux moyens d'envoi (214), dans lequel les signaux de programmes numériques conditionnés reçus sont triés et au moins un signal de programme numérique est séparé des signaux de programmes numériques conditionnés reçus.

3. Système selon la revendication 1 ou 2, dans lequel la première tête de câble (208) comporte :

un processeur (209), relié fonctionnellement à la première antenne-satellite, dans lequel les signaux de programmes numériques reçus sont traités de manière à former un ensemble de signaux de programmes numériques triés, et les signaux de programmes numériques triés formant un sous-ensemble des signaux de programmes numériques reçus ; et des moyens (214), reliés fonctionnellement au processeur (209), pour envoyer le sous-ensemble de signaux de programmes numériques triés à partir du processeur (209) vers les sites abonnés.

4. Système selon la revendication 2 ou 3, dans lequel le premier terminal (220) comporte en outre un port d'entrée (652), dans lequel les signaux de programmes numériques triés sont reçus par le premier terminal (220).

5. Système selon l'une quelconque des revendications 2 à 4, dans lequel des signaux de programmes locaux sont utilisés dans la première tête de câble (208), la première tête de câble (208) comportant en outre un processeur de signaux (209), relié fonctionnellement à la première antenne satellite et aux moyens d'envoi (214), les signaux de programmes locaux pouvant être insérés parmi les signaux de programmes numériques conditionnés.

6. Système selon l'une quelconque des revendications 1 à 5, dans lequel le central (202) comporte en outre un ordinateur, dans lequel l'ordinateur envoie des directives à la première tête de câble (208), en association avec les signaux de programmes numériques, qui permettent au processeur de signaux (209) de contrôler l'insertion de signaux de programmes locaux dans la première tête de câble (208).

7. Système selon la revendication 6, dans lequel un port situé dans le premier terminal (220) reçoit les signaux de programmes numériques triés et les signaux de programmes locaux insérés par le processeur de signaux (209).

8. Système selon l'une quelconque des revendications 1 à 7, dans lequel le système comporte en outre un second répéteur-satellite et une seconde tête de câble, les premier et second répéteurs étant utilisés pour transmettre un premier et un second groupe de signaux de programmes numériques vers les têtes de câble, le central (202) comportant en outre un processeur (209), les premier et second groupes de signaux de programmes numériques étant alloués à des fins de transmission vers le premier ou second répéteur-satellite, et chaque répéteur-satellite recevant un groupe différent de signaux de programmes numériques.

9. Système selon la revendication 8, dans lequel le central (202) comporte en outre :

un premier émetteur, dans lequel le premier groupe de signaux de programmes numériques est émis vers le premier répéteur-satellite, et la première tête de câble (208) recevant les signaux de programmes numériques en provenance du premier répéteur-satellite ; et

un second émetteur, dans lequel le second groupe de signaux de programmes numériques est émis vers le second répéteur-satellite, et la seconde tête de câble recevant les signaux de programmes numériques en provenance du second répéteur-satellite.

10. Système selon l'une quelconque des revendications 1 à 9, dans lequel les signaux de programmes numériques sont constitués à la fois de signaux audio et vidéo, et plus d'un canal audio peut exister pour un signal vidéo, dans lequel la première antenne-satellite située dans la première tête de câble (208) reçoit les signaux vidéo et audio en provenance du premier répéteur-satellite, et dans lequel un signal vidéo particulier peut être associé à de multiples canaux audio, la première tête de câble (208) comportant en outre un contrôleur, dans lequel le contrôleur sélectionne un ou plusieurs canaux audio reçus de manière à le ou les faire correspondre au signal vidéo particulier, un auditeur recevant au moins un canal audio sélectionné.

11. Système selon la revendication 10, dans lequel plus d'une langue est représentée parmi les multiples canaux audio associés au signal vidéo particulier, et dans lequel la première tête de câble (208) reçoit des informations en provenance des sites abonnés, le contrôleur installé au niveau de la première tête de câble (208) comportant

en outre des moyens pour sélectionner un canal audio particulier en réponse aux informations reçues en provenance du site abonné.

12. Système selon la revendication 11, dans lequel le premier terminal (220) comporte en outre :

des moyens (640) pour afficher des menus d'options de langues à l'abonné ; et
une interface (626), dans laquelle les sélections-menus entrées par l'abonné sont reçues, et
dans lequel les informations reçues au niveau de la première tête de câble (208) à partir du site abonné
incluent la sélection-menu effectuée par l'abonné en réponse aux options de langues affichées par le menu
en utilisant l'interface (626).

13. Système selon l'une quelconque des revendications 1 à 12, dans lequel un second satellite est utilisé, la première tête de câble (208) comportant en outre une seconde antenne-satellite, la seconde antenne-satellite recevant les signaux de programmes numériques en provenance d'un second répéteur-satellite.

14. Système selon l'une quelconque des revendications 1 à 13, dans lequel un premier et un second groupe de terminaux sont desservis par la première tête de câble (208), le premier groupe de terminaux recevant les signaux de programmes numériques en provenance du premier répéteur-satellite via la première antenne-satellite, et le second groupe de terminaux recevant les signaux de programmes numériques en provenance d'un second répéteur-satellite via une seconde antenne-satellite, et dans lequel au moins l'un des signaux de programmes numériques reçus en provenance du premier répéteur-satellite diffère des signaux de programmes numériques reçus en provenance du second répéteur-satellite.

15. Système selon l'une quelconque des revendications 2 à 14, dans lequel les signaux de programmes numériques contiennent plus d'un programme audio/vidéo numérique, le processeur (209) installé dans la première tête de câble (208) comportant des moyens pour séparer des programmes audio/vidéo numériques individuels à partir des signaux de programmes numériques reçus en provenance du premier répéteur-satellite par la première antenne-satellite.

16. Système pour délivrer des signaux de programmes numériques à partir d'un central (202) auprès de sites abonnés en utilisant un satellite (206) avec des répéteurs-satellites, dans lequel les signaux de programmes numériques sont envoyés vers les sites abonnés via un système satellite, le système comportant :

un central (202), localisé à distance des sites abonnés, dans lequel plus d'un signal de programmes numériques est traité à des fins de transmission vers un premier répéteur-satellite, les signaux de programmes numériques étant conditionnés et complétés par un signal d'informations de contrôle de programmes avant ladite transmission ;
une première antenne-satellite, installée dans un premier site abonné, par laquelle les signaux de programmes numériques sont reçus en provenance du premier répéteur-satellite ; et
un premier terminal (220), installé dans un premier site abonné, et relié à la première antenne-satellite, dans lequel les signaux de programmes numériques sont reçus et au moins un signal de programme numérique est traité de manière à ce que l'abonné puisse regarder le programme.

17. Système selon la revendication 16, dans lequel le système comporte en outre un second répéteur-satellite et un second terminal, les premier et second répéteurs étant utilisés pour transmettre un premier et un second groupe de signaux de programmes numériques aux terminaux, le central (202) comportant en outre un processeur (209), les premier et second groupes de signaux de programmes numériques étant alloués à des fins de transmission au premier ou second répéteur-satellite, et chaque répéteur-satellite recevant un groupe différent de signaux de programmes numériques.

18. Système selon la revendication 17, dans lequel le central (202) comporte en outre :

un premier émetteur, par lequel le premier groupe de signaux de programmes numériques est émis vers le premier répéteur-satellite, et le premier terminal (220) recevant les signaux de programmes numériques en provenance du premier répéteur-satellite via la première antenne-satellite ; et
un second émetteur, par lequel le second groupe de signaux de programmes numériques est émis vers le second répéteur-satellite, et le second terminal recevant les signaux de programmes numériques en provenance du second répéteur-satellite via la seconde antenne-satellite.

19. Système selon l'une quelconque des revendications 1 à 18, dans lequel le central (202) comporte en outre un processeur (209), dans lequel un signal d'informations de contrôle de programmes est généré, lequel est utilisé par le premier terminal (220).
- 5 20. Système selon l'une quelconque des revendications 1 à 19, dans lequel un signal d'informations de contrôle de programmes est conditionné avec les signaux de programmes numériques.
21. Système selon la revendication 19 ou 20, dans lequel le premier terminal (220) comporte en outre des moyens pour générer des affichages menu en utilisant le signal d'informations de contrôle de programmes.
- 10 22. Système selon l'une quelconque des revendications 19 à 21, dans lequel le signal d'informations de contrôle de programmes inclut des données relatives aux titres des programmes.
23. Système selon l'une quelconque des revendications 19 à 22, dans lequel le signal d'informations de contrôle de programmes inclut des données relatives aux horaires de début des programmes.
- 15 24. Système selon l'une quelconque des revendications 19 à 23, dans lequel le signal d'informations de contrôle de programmes inclut des données relatives aux menus.
- 20 25. Système selon l'une quelconque des revendications 19 à 24, dans lequel le signal d'informations de contrôle de programmes inclut des données relatives à des listes de programmes pour plus d'un canal de programmation.
26. Système selon l'une quelconque des revendications 1 à 25, dans lequel le central (202) comporte en outre un compresseur, dans lequel les signaux de programmes numériques sont compressés avant transmission vers le premier répéteur-satellite.
- 25 27. Système selon l'une quelconque des revendications 1 à 26, dans lequel le premier terminal (220) inclut un décompresseur (618), dans lequel les signaux de programmes numériques reçus sont décompressés afin d'être affichés à l'abonné.
- 30 28. Dispositif selon l'une quelconque des revendications 1 à 27, dans lequel le premier terminal (220) comprend un terminal ST numérique, dans lequel le terminal ST numérique étant utilisé dans le site abonné, et le terminal ST numérique décompressant les signaux de programmes numériques envoyés.
- 35 29. Système selon l'une quelconque des revendications 1 à 28, dans lequel le premier terminal (220) comprend un terminal ST, et le terminal ST étant relié fonctionnellement à une télévision (222).
30. Système selon l'une quelconque des revendications 1 à 29, dans lequel le premier terminal (220) comprend une carte électronique (700) insérable.
- 40 31. Système selon l'une quelconque des revendications 1 à 30, dans lequel le premier terminal (220) comporte en outre un processeur (602), dans lequel les signaux de programmes numériques sont convertis en signaux de programmes analogiques à des fins d'affichage dans le site abonné.
- 45 32. Système selon l'une quelconque des revendications 1 à 31, dans lequel les signaux de programmes numériques sont constitués de signaux audio numériques, le premier terminal (220) comportant :
des moyens (603) pour recevoir les signaux audio numériques ; et
des moyens (612) pour délivrer en sortie les signaux audio numériques auprès d'un auditeur.
- 50 33. Système selon la revendication 32, dans lequel le système comporte en outre un troisième terminal, relié au premier terminal (220), et localisé à distance du premier terminal (220), dans lequel les signaux audio numériques sont reçus et émis auprès de l'auditeur.
- 55 34. Système selon la revendication 33, dans lequel le troisième terminal délivre en sortie des signaux audio numériques, et le premier terminal (220) délivre en sortie d'une manière concurrente des signaux audio et vidéo numériques de manière à ce que l'abonné puisse regarder un programme.

35. Système selon l'une quelconque des revendications 1 à 34, dans lequel le central (202) comprend un récepteur qui reçoit les signaux de programmes numériques en provenance d'une source de programmes externe.

5 36. Système selon l'une quelconque des revendications 1 à 35, dans lequel le central (202) est capable de convertir les signaux analogiques reçus en provenance d'une source de programmes externe en signaux numériques avant d'envoyer les signaux de programmes numériques à partir du central (202) vers les sites abonnés, le central (202) comportant en outre :

10 un récepteur, dans lequel les signaux analogiques sont reçus en provenance de sources de programmes externes ; et

un convertisseur, dans lequel les signaux analogiques reçus sont convertis en signaux de programmes numériques.

15 37. Système selon l'une quelconque des revendications 1 à 36, dans lequel le central (202) comporte en outre un processeur (209), dans lequel les signaux de programmes numériques sont conditionnés à des fins de transmission vers le premier répéteur-satellite, et les signaux conditionnés incluant au moins un signal de programme numérique.

20 38. Système selon l'une quelconque des revendications 1 à 37, dans lequel le central (202) joue le rôle de central maître, le système comportant en outre un central esclave, relié fonctionnellement au central maître, les fonctions du central esclave étant coordonnées avec le central maître.

39. Système selon la revendication 38, dans lequel le central maître contrôle les fonctions du central esclave.

25 40. Système selon l'une quelconque des revendications 1 à 39, dans lequel une seconde antenne-satellite reçoit les signaux de programmes numériques en provenance du premier répéteur-satellite.

30 41. Système selon l'une quelconque des revendications 1 à 40, le système comportant en outre un site de liaison montante, relié fonctionnellement au central (202), dans lequel les signaux de programmes numériques traités sont émis vers le premier répéteur-satellite.

42. Système selon la revendication 41, dans lequel le nombre de sites de liaison montante est supérieur à un, et au moins un site de liaison montante est localisé à distance du central (202).

35 43. Système selon l'une quelconque des revendications 1 à 42, comportant en outre une télécommande (900) comportant une pluralité de boutons de sélection-menu.




Fig. 1





Fig. 3




Fig. 4




Fig. 5a




Fig. 5b




Fig. 6




Fig. 7a





Fig. 7b






Fig. 8




Fig. 9a




Fig. 9b




Fig. 9c